



SOLVENT / STRIPPER



686 S. Adams Street · Kansas City, KS 66105
(913) 321-9000

PRODUCT DATA SHEET

1. PRODUCT DESCRIPTION

VersaFlex Dzolv is a water soluble, organic solvent containing no aromatics or petroleum distillates. **Dzolv** is designed to provide maximum stripping effectiveness while incorporating a high flash point and low toxicity. **Dzolv** replaces most industrial solvents such as chlorinated hydrocarbons (methylene chloride, carbon tetrachloride and 1,1,1 trichlorethane) when used on cured polymers.

2. USES

VersaFlex Dzolv solvent/stripper is designed to strip polyurea, polyurethane, epoxies and polyester resins.

Effective with:

- Grease
- Oil
- Inks
- Waxes
- Rubber residues
- Lacquers
- Latex paint
- Oil based paint

Advantages:

- VOC level acceptable to SCAQMD region
- Non toxic
- Easy to apply
- Flash point >200°F
- Low odor
- Indefinite shelf life
- Will not cause hazardous polymerization
- Low evaporation rate
- Not R.C.R.A or DOT regulated. Dzolv's water solubility allows for safe use.

3. PHYSICAL PROPERTIES

Appearance	Clear liquid
Odor	Mild sweet odor
Specific Gravity @ 77°F	1.08
Flash Point	> 200°F

The value ranges stated in this Technical Data Sheet are based on system processing under laboratory conditions. Equipment configurations and/or field application conditions may produce variances in final system values.

4. LIMITATIONS

Reacts violently with strong acids or bases.

5. PACKAGING

- **55 Gallon:** 55 gallon drum. Drum containers filled by weight; volume is closely approximated.
- **5 Gallon:** 5 gallon container.
- **1 Gallon:** 1 Gallon container.

6. PREPARATION & APPLICATION

Apply **Dzolv** liberally or employ baths where possible for stationery stripping. May be applied by brush. May be used to strip various gun parts – Consult **VersaFlex**. Not recommended for flushing plural component machines.

7. SAFETY

Review SDS at www.versaflex.com. Basic safety for personal protection is:

- Long sleeve overalls or disposable Tyvek overalls
- Rubber gloves
- Splash shield or safety glasses with splash guards
- Rubber or leather boots
- Respirator
- Do not use near high heat or open flame
- Do not take internally
- Keep out of reach of children

8. PRECAUTION

This product contains Volatile Organic Compounds (VOC's) which may be released during and for some period after installation producing odors and affecting air quality. To avoid possible contamination of sensitive substances and for protection of human health, ensure proper air ventilation of work areas until odors completely dissipate.

9. SHELF LIFE

One year from shipment date, in original, unopened factory containers, under normal storage conditions of 55°F to 95°F (18° - 35°C).

10. TECHNICAL SERVICES

Sales and Customer Support: (913) 321-9000.

11. WARRANTY

During a period of one-year from date of shipping, VersaFlex Incorporated will refund the price of or replace, at its election, product it finds to be defectively manufactured, provided the product has been stored and used properly. Except as expressly stated herein, the company makes no warranty of merchantability and no warranty of fitness for any particular purpose, nor does it make any warranty, expressed or implied, of any nature whatsoever with respect to the product or its use. In no event shall the company be liable for delay caused by defects, for loss of use, for indirect, special or consequential damages, or for any charges or expenses of any nature incurred without its written consent.