SAFETY DATA SHEET



Section 1. Identification

Product Name: VF 30 (B-Side) VersaFlex Incorporated 9777 West Gulf Bank Houston, TX 77040 713-466-4988

Spill, leak, fire, exposure, or accident, call CHEMTREC day or night Domestic North America 800.424.9300

e-mail: ehs@versaflex.com

International 703.527.3887

Section 2. Hazards Identification

GHS Ratings:

Oral Toxicity Acute Tox. 4 Oral>300+<=2000mg/kg Inhalation Toxicity Acute Tox. 4 Gases>2500+<=5000ppm, Vapors>10+<=20mg/l, Dusts&mists>1+<=5mg/l 2 Skin corrosive Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation Eye corrosive 2A Eye irritant: Subcategory 2A, Reversible in 21 days Skin sensitizer Skin sensitizer 1 Reproductive toxin 2 Human or animal evidence possibly with other information

<u>GHS Hazards</u>	
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361	Suspected of damaging fertility or
	the unborn child

GHS Precautions	<u>5</u>
P201	Obtain special instructions before use
P202	Do not handle until all safety
	precautions have been read and
	understood
P261	Avoid breathing
	dust/fume/gas/mist/vapours/spray
P264	Wash exposed skin thoroughly after
	handling
P270	Do not eat, drink or smoke when using
	this product
P271	Use only outdoors or in a well-ventilated
	area
P272	Contaminated work clothing should not
	be allowed out of the workplace
P280	Wear protective gloves/protective
D004	clothing/eye protection/face protection
P281	Use personal protective equipment as
D040	required
P312	Call a POISON CENTER or
Daga	doctor/physician if you feel unwell
P321	Specific treatment (as detailed on this
	label)
I	

SDS for: VF 30 (B-Side) Page 1 of 8

P330	Rinse mouth
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel
P302+P352	IF ON SKIN: Wash with soap and water
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P33	IF IN EYES: Rinse continuously with
8	water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P405	Store locked up
P501	Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Warning



Section 3. Composites/Information on Ingredients

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Benzyl alcohol 0000100-51-6 40 to 50%	OELs not established	OELs not established	
Tall oil fatty acids, reaction product with Tetraethylene pentamine 68953-36-6 20 to 30%	OELs not established	OELs not established	
Trade Secret 10 to 20%	OELs not established	OELs not established	
Phenol, 4-nonyl-, branched 84852-15-3 5 to 10%	OELs not established	OELs not established	

SDS for: VF 30 (B-Side) Page 2 of 8

Siloxanes and Silicones, dimethyl, vinyl group- terminated 68083-19-2 5 to 10%	OELs not established	OELs not established	
2,4,6-Tri (dimethylaminomethyl)phenol 90-72-2 1 to 5%	OELs not established	OELs not established	
Siloxanes and Silicones, dimethyl, methyl hydrogen 68037-59-2 0.1 to 1.0%	OELs not established	OELs not established	
Tetraethylenepentamine 112-57-2 0.1 to 1.0%	OELs not established	OELs not established	
Ethylbenzene 100-41-4 0.0 to 0.1%	PELs - 100 ppm TWA PELs - 435 mg/m3 TWA vPELs - 125 ppm STEL vPELs - 545 mg/m3 STEL	TLV - 20 ppm TWA	

Section 4. First-aid Measures

Move exposed person to fresh air. If breathing is labored, oxygen should be administered by qualified personnel.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

After contact with skin, wash immediately with plenty of warm, soapy water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Provided the patient is conscious, wash out mouth with water. Get medical attention if symptoms appear.

Section 5. Fire-fighting Measures

Extinguishing Media: Water, Foam, CO2 or dry powder.

Caution:

Heating or fire can release toxic gas.

Hazardous decomposition products:

Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, and hydrocarbons.

Special protective actions for fire-fighters:

Promptly isolate the scene by removing all persons from the vicinity of the incident, if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. PVC boots, gloves, safety helmet and protective clothing should be worn.

Section 6. Accidental Release Measures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled

SDS for: VF 30 (B-Side) Page 3 of 8

material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and Storage

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not get into eyes.

Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and may be hazardous.

Material is to be stored in accordance with local regulations. Store in original container protected from direct sunlight in a dry and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers.

Use appropriate containment to avoid environmental contamination.

Unsuitable containers: Do not store in containers made of copper, copper alloys or galvanized surfaces.

Section 8. Exposure Controls/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Benzyl alcohol 0000100-51-6	OELs not established	OELs not established	
Tall oil fatty acids, reaction product with Tetraethylene pentamine 68953-36-6	OELs not established	OELs not established	
Trade Secret N/A	OELs not established	OELs not established	
Phenol, 4-nonyl-, branched 84852-15-3	OELs not established	OELs not established	
Siloxanes and Silicones, dimethyl, vinyl group- terminated 68083-19-2	OELs not established	OELs not established	

SDS for: VF 30 (B-Side) Page 4 of 8

2,4,6-Tri (dimethylaminomethyl) phenol 90-72-2	OELs not established	OELs not established	
Siloxanes and Silicones, dimethyl, methyl hydrogen 68037-59-2	OELs not established	OELs not established	
Tetraethylenepentamine 112-57-2	OELs not established	OELs not established	
Ethylbenzene 100-41-4	PELs - 100 ppm TWA PELs - 435 mg/m3 TWA vPELs - 125 ppm STEL vPELs - 545 mg/m3 STEL	TLV - 20 ppm TWA	

Engineering Controls: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Smell is not an adequate indicator of hazard.

Ventilation: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Protective Gear: In case of inadequate ventilation, wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9. Physical and Chemical Properties

Appearance: Pale yellow to amber	Odor: Faint odor	
Vapor Pressure: No Data	Odor threshold: No Data	
pH: No Data	Melting point: No Data	
Freezing point: No Data	Flash point: 208 F,98 C	
Evaporation rate: No Data	Flammability: No Data	
Explosive Limits: No Data	Vapor pressure: No Data	
Vapor Density: No Data	Specific Gravity 0.98	
Solubility: No Data	Partition coefficient (n- No Data octanol/water):	
Boiling range: No Data	Autoignition temperature: No Data	
Decomposition temperature: No Data	Viscosity: N/A	
% Weight Volatile (VOC) 48.52		

SDS for: VF 30 (B-Side) Page 5 of 8

Section 10. Stability and Reactivity

Chemical Stability: Stable at room temperature. No specific test data related to reactivity is available for this product or its ingredients.

Hazardous reactions: None known. Stable under normal conditions.

Section 11. Toxicological Information

Routes of Entry

Inhalation Skin Contact Eye Contact Ingestion

Target Organs

Eyes Central Nervous System Skin Cholinesterase Respiratory System

Effects of Overexposure

Carcinogenicity

CAS NumberDescription% WeightCarcinogen Rating100-41-4Ethylbenzene0.0 to 0.1%Ethylbenzene:

Section 12. Ecological Information

Only component information is listed, if any. No testing has been performed on this mixture as it relates to ecological impact.

Component Ecotoxicity

Benzyl alcohol 96 Hr LC50 Pimephales promelas: 460 mg/L [static]; 96 Hr LC50 Lepomis

macrochirus: 10 mg/L [static]; 48 Hr EC50 water flea: 23 mg/L

Phenol, 4-nonyl-, branched 96 Hr EC50 Pseudokirchneriella subcapitata: 0.36 - 0.48 mg/L [static]; 72 Hr

EC50 Pseudokirchneriella subcapitata: 0.16 - 0.72 mg/L [static]; 72 Hr EC50 Desmodesmus subspicatus: 1.3 mg/L; 96 Hr LC50 Pimephales promelas: 0.135 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 0.1351 mg/L [flow-through]

; 48 Hr EC50 Daphnia magna: 0.14 mg/L

Tetraethylenepentamine 72 Hr EC50 Pseudokirchneriella subcapitata: 2.1 mg/L; 96 Hr LC50 Pseudokirchner

reticulata: 420 mg/L [static]; 48 Hr EC50 Daphnia magna: 24.1 mg/L

Ethylbenzene 72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50

Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella

subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella

subcapitata: 1.7 - 7.6 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static]; 48 Hr EC50

Daphnia magna: 1.8 - 2.4 mg/L

Section 13. Disposal Considerations

The generation of waste should be avoided or minimized by using excess product in an alternate, beneficial application wherever possible.

Empty containers may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

SDS for: VF 30 (B-Side) Page 6 of 8

Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport Information

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Agency	Proper Shipping Name	UN Number	Packing Group	Hazard Class
DOT	Environmentally hazardous substance, liquid, n.o.s.	UN3082	III	9
	"Phenol, 4-nonyl-,branched" Marine pollutant			
	Non-bulk packages are not regulated, unless transported b	y inland waterwa	ıy.	
IATA	Environmentally hazardous substance, liquid, n.o.s.	UN3082	III	9
	"Phenol, 4-nonyl-,branched" Marine pollutant			
	Quantity limitations: 450 L			
IMDG	Environmentally hazardous substance, liquid, n.o.s.	UN3082	III	9
	"Phenol, 4-nonyl-,branched" Marine pollutant			
	Marine pollutant mark is not required when transported in s	izes <5L or <5 kg	g	

Section 15. Regulatory Information

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None





WHMIS Symbol(s)

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30, unless listed below:

- None

This product contains the following substance(s), which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372:

- None

100-41-4 Ethylbenzene 0.0 - 0.1%

SDS for: VF 30 (B-Side) Page 7 of 8

Section 16. Other Information


The customer is responsible for determining the proper PPE code for this material within their respective process.

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating
Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE



Date revised: 2015-10-06 Reviewer Revision 5

Notice to reader:

Date Prepared: 10/6/2015

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PUPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

SDS for: VF 30 (B-Side) Page 8 of 8