

1. Product and Company Identification

Product Name: GELFLEX® 1115 (A-Side)

VersaFlex / Raven Lining Systems 686 South Adams Street Kansas City, KS 66105

www.versaflex.com / www.ravenlining.com

Company Phone: (913) 321-9000 Company Toll Free: (800) 324-2810

CHEMTREC 24 hour Emergency USA: (800) 424-9300 CHEMTREC 24 hour International: (703) 527-3887

Product Use: Primer / Sealer / Coating / Lining Not recommended for: Non Professional Use

2. Hazards Identification

Signal Word: Danger





GHS Ratings:

Inhalation Toxicity Acute Tox. 4 Gases>2500+<=5000ppm, Vapors>10+<=20mg/l,

Dusts&mists>1+<=5mg/l

Respiratory sensitizer 1 Respiratory sensitizer.

Skin sensitizer 1 Skin sensitizer.

Mutagen 2 Suspected/Possible: May include heritable mutations in human

germ cells, Positive evidence from tests in mammals and somatic cell tests, In vivo somatic genotoxicity supported by in

vitro mutagenicity.

GHS Hazards

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.

GHS Precautions

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P285 In case of inadequate ventilation wear respiratory protection.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P321 Specific treatment (see Section 4 of the SDS).

P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with soap and water.
P304+P340	IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P405	Store locked up.
P501	Dispose of contents/container according to Section 13 of the SDS.

3. Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Hexamethylene Diisocyanate Homopolymer	28182-81-2	70 - 80%
Aliphatic Polyisocyanate based on HDI	666723-27-9	10 - 20%
Neodecanoic acid, oxiranylmethyl ester	26761-45-5	5 - 10%

4. First Aid Measures

Inhalation: Remove to fresh air if effects occur. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Consult a physician or transport to a medical facility.

Eye Contact: Immediately flush eyes with large quantities of water for at least 15 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Skin Contact: Wash immediately and thoroughly with soap and lukewarm flowing water. Remove contaminated clothing while washing. Seek medical attention if irritation develops and persists. This compound is a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Cholinesterase inhibition has been noted in human exposure but is not of benefit in determining exposure and is not correlated with signs of exposure. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

5. Fire Fighting Measures

Flash Point: >126 C (>259 F)

Flammable Properties: Product is not considered a fire hazard, but will burn if ignited. NFPA Flammability Class: III B (Combustible liquid).

Suitable Extinguishing Media: Carbon dioxide, dry chemical, water fog or fine spray. Alcohol resistant foams are preferred, general purpose synthetic foams or protein foams may function, but will not be as effective. Unsuitable Extinguishing Media: Do not use direct water stream, as it may spread fire.

SDS for: GELFLEX® 1115 (A-Side)

Unusual Fire and Explosion Hazards: Product reacts with water. Reaction may produce heat and/or gases. This reaction may be violent. Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides, isocyanates, hydrogen cyanide and other unidentified toxic and/or irritating compounds.

Fire Fighting: Stay upwind and keep people away. Isolate fire and deny unnecessary entry. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out. Contain fire water run-off if possible, as it may cause environmental damage. Review section 6 and section 12 of this SDS.

Protection of Firefighters: Wear positive pressure self-contained breathing apparatus (SCBA) and approved protective clothing (helmet, coat, trousers, boots and gloves). If contact is likely, use full chemical resistant fire fighting clothing with SCBA.

6. Accidental Release Measures

Personal Precautions: Put on appropriate personal protective equipment (see section 8).

Environmental Precautions: Prevent spilled material from contact with soil, drains and sewers.

Methods for Containment: Contain by diking with sand, earth or other suitable material.

Methods for Clean-up: Absorb spill with an inert material, use non-sparking tools to place into labeled waste container for disposal.

7. Handling and Storage

Handling: Wear appropriate personal protective equipment (see section 8). Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Do not ingest. Avoid prolonged or repeated contact with skin. May cause allergic skin reaction, persons with a history of skin sensitization should not be employed in any process in which this product is used. Wash thoroughly with soap and water after handling. Do not handle or store near flame, heat or strong oxidants. Keep away from sources of ignition and hot metal surfaces.

Storage: Store original unopened containers in a sheltered area between 60°F and 80°F (15°C and 27°C) at atmospheric pressure. Do not store in direct sunlight. Keep containers closed when not in use.

8. Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Hexamethylene Diisocyanate Homopolymer 28182-81-2	Not Established	Not Established	Not Established
Aliphatic Polyisocyanate based on HDI 666723-27-9	Not Established	Not Established	Not Established
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	Not Established	Not Established	Not Established

Engineering Controls: General mechanical ventilation is sufficient for most conditions. Control airborne levels below the exposure guidelines, if established.

Local exhaust ventilation may be necessary for some operations.

General Hygiene Considerations: Wash thoroughly after handling and before eating, drinking or smoking.

Eye/face Protection: Use chemical safety glasses, splash-proof eye goggles or goggles with full faceshield.

Skin Protection: Use neoprene, nitrile/butadiene rubber or other impermeable chemical resistant gloves to prevent skin irritation. If potential for skin contact is present, wear impervious, long-sleeved, body covering clothing and rubber boots.

Respiratory Protection: If exposure may or does exceed occupational exposure limits, respiratory irritation is

experienced, or during spray application, use a properly fitted MSHA/NIOSH approved respirator fitted with organic vapor cartridges and particulate pre-filters. If the respirator is the sole means of protection, use a full-face supplied air respirator. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use an approved positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). If sanding or grinding on cured material, use above respirator fitted with HEPA filters or a dust mask.

Contaminated Gear: Remove contaminated clothing and shoes while washing. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

9. Physical and Chemical Properties

Appearance Clear to pale yellow

Odor Threshold No data found

pH No data found

Boiling Point 251°C

Flash Point 259°F, 126°C

Flammability (solid, gas) No data found

Vapor Pressure No data found

Specific Gravity 1.1 - 1.2

Partition Coefficient No data found (n-octanol/water)

Decomposition Temperature No data found

Lbs VOC/Gallon Less Water 0.0

Odor Mild

Physical State Liquid

Melting/Freezing Point No data found

Boiling Range No data found

Evaporation Rate No data found

LEL/UEL No data found

Vapor Density No data found

Solubility in Water No data found

Autoignition Temperature No data found

Viscosity No data found

10. Stability and Reactivity

Chemical Stability: Stable under recommended storage conditions (see Section 7).

Conditions to Avoid: Avoid temperatures above 450 deg F (230 deg C), potential violent decomposition may occur. Avoid contact with water, as material reacts with water, releasing carbon dioxide which can cause rapid pressure buildup and rupture of closed containers. Elevated temperatures accelerate this reaction.

Incompatible Materials: Strong acids, bases, or oxidizing agents. Avoid unintended contact with amines, alcohols, water, moist air and metals such as aluminum, brass, copper, tin, zinc and galvanized metals.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides, isocyanates, hydrogen cyanide and other unidentified toxic and/or irritating compounds.

Hazardous polymerization will not occur.

11. Toxicological Information

Mixture Toxicity

Inhalation Toxicity LC50: 4mg/L

Component Toxicity

26761-45-5 Neodecanoic acid, oxiranylmethyl ester

Dermal LD50: 3,800 mg/kg (Rat) Inhalation LC50: 0 mg/L (Rat)

Likely Routes of Exposure:

No data found

Target Organs

May cause damage to the following organs:

No data found

Effects of Overexposure

CAS Number Description % Weight Carcinogen Rating

SDS for: GELFLEX® 1115 (A-Side)

None No data found

12. Ecological Information

Component Ecotoxicity

Neodecanoic acid, oxiranylmethyl

96 Hr LC50 Oncorhynchus mykiss: 5 mg/L [semi-static]

48 Hr EC50 Daphnia magna: 4.8 mg/L

96 Hr EC50 Pseudokirchneriella subcapitata: 3.5 mg/L

13. Disposal Considerations

Waste Disposal Methods: Dispose of in accordance with federal, state and local regulations. The preferred method for disposal of uncontaminated product is by recycling, reclaiming, incineration or other thermal destruction device using a licensed and permitted waste disposal contractor.

14. Transport Information

For DOT shipments in containers larger than 119 gallons (450L) containing Neodecanoic acid, oxiranylmethyl ester, the proper shipping information is:

Proper shipping name: Environmentally Hazardous Substance, Liquid, n.o.s.(Neodecanoic acid,

oxiranylmethyl ester) UN number: UN3082 Packing Group: III

Class: 9

For containers less than 119 gallons (450L), such as drums and pails; this material is Not Regulated for DOT surface shipping.

<u>Agency</u> DOT	<u>Proper Shipping Name</u> Not Regulated	<u>UN Number</u>	Packing Group	<u>Hazard Class</u>
	Non-bulk packages are not regulated, unless transported	d by inland wate	erway.	
ICAO/IATA	Environmentally Hazardous Substance, Liquid, n.o.s. (Neodecanoic acid, oxiranylmethyl ester)	UN3082	III	9
	Quantity Limitations: 450 L			
IMDG	Environmentally Hazardous Substance, Liquid, n.o.s. (Neodecanoic acid, oxiranylmethyl ester)	UN3082	III	9
	Marine pollutant mark is not required when transported in	n sizes <5L or <	<5 kg	
TDG	Environmentally Hazardous Substance, Liquid, n.o.s. (Neodecanoic acid, oxiranylmethyl ester)	UN3082	III	9

15. Regulatory Information

USA Federal: This SDS has been prepared in compliance with the Occupational Safety and Health Act (OSHA) Hazard Communication Standard (29 CFR 1910.1200). This product is considered to be a hazardous chemical under that standard. The specific chemical identity and/or exact percentage of any proprietary ingredient(s) may be withheld as a trade secret, pursuant to the standard.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): To the best of our knowledge, this product contains the following chemicals which are known to the State of California to cause cancer, developmental or reproductive toxicity at levels which require warning under this statute:

- None

USA Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) - section 103 Hazardous Substances Reportable Quantities (RQs): To the best of our knowledge, this product contains the following chemicals which are listed in 40 CFR 302.4:

- None

Massachusetts Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

New Jersey Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

Pennsylvania Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

USA Resource Conservation and Recovery Act (40 CFR 261): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

USA Superfund Amendments and Reauthorization Act (SARA) of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 313 Toxic Release Inventory (TRI) Form R: To the best of our knowledge, this product contains the following chemicals which are listed in 40 CFR 372.65:

- None

USA Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 302 Extremely Hazardous Substances Threshold Planning Quantities (TPQs): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

USA Toxic Substances Control Act (TSCA) - section 12(b): To the best of our knowledge, this product contains the following chemicals above the de minimus concentration(s) which requires notification to the Environmental Protection Agency (EPA) per 40 CFR 707, subpart D, if any person intends to export:

- None

Country	<u>Regulation</u>	All Components Listed
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Canada Domestic Substance List	Yes
Canada	Canada Non-Domestic Substances List (NDSL)	No
China	China Inventory of Existing Chemical Substances	No
EU	EU REACH List of Registered Intermediates	No
EU	EU REACH List of Pre-Registered Substances	No
EU	EU REACH List of Registered Substances	No
Japan	Japanese Existing and New Chemical Substances List	No
South Korea	South Korea Existing Chemicals Inventory	No
Philippines	Philippines Inventory of Chemicals and Chemical	Yes
USA	USA TSCA Inventory list section 8(b)	Yes

- None

16. Other Information

Legend

ACGIH American Conference of Governmental Industrial Hygienists. Inc.

ADR/RID European Agreement for transport of dangerous goods by road (ADR) and by rail (RID)

CAS No. Chemical Abstract Service Registry Number

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act, AKA "Superfund"

DOT Department of Transportation (USA)

HCS OSHA Hazard Communication Standard (29 CFR 1910.1200)

IARC International Agency for Research on Cancer
IATA International Air Transport Association
ICAO International Civil Aviation Organization
IMO International Maritime Organization
IMDG International Maritime Dangerous Goods
MSHA Mine Safety and Health Administration

N.A. Not ApplicableN.D. Not DeterminedN.E. Not Established

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration (USA)

PEL Permissible Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986 (40 CFR)
STEL Short Term Exposure Limit (15 minute Time Weighted Average)

TDG Canada Transport of Dangerous Goods regulations

TLV Threshold Limit Value TWA Time Weighted Average

WHMIS Canada Workplace Hazardous Materials Information System

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)




HMIS & NFPA Hazard Rating Legend
* = Chronic Health Hazard

0 = INSIGNIFICANT 1 = SLIGHT

2 = MODERATE

3 = HIGH



Disclaimer

VERSAFLEX / RAVEN LINING SYSTEMS (VF/RLS) MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO ANY INFORMATION PRESENTED HEREIN, ALL OF WHICH IS PROVIDED "AS IS". TO THE MAXIMUM EXTENT PERMITTED BY LAW, VF/RLS EXPRESSLY EXCLUDES ALL WARRANTIES, OBLIGATIONS, REPRESENTATIONS, LIABILITIES, TERMS AND CONDITIONS (WHETHER THEY ARE EXPRESS OR IMPLIED, OR ARISE IN CONTRACT, STATUTE, OR OTHERWISE, AND IRRESPECTIVE OF THE NEGLIGENCE OF VF/RLS, ITS EMPLOYEES OR AGENTS) IN CONNECTION WITH THE INFORMATION PRESENTED HEREIN. VF/RLS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO MERCHANTABILITY, FITNESS FOR PURPOSE, NONINFRINGEMENT OR CONFORMITY WITH DESCRIPTION OR SAMPLE.

Reviewer Revision

Date Prepared: 1/3/2019