



AC 200

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

GHS product identifier: AC 200

Other means of identification: Coating, Acrylic resin, Priming

Recommended use of the chemical and restrictions on use: N/A

Supplier's details: VANBERG SPECIALIZED COATINGS
10705 COTTONWOOD ST.
LENEXA, KS 66215
INFORMATION PHONE NUMBER: 913-599-5939

Emergency phone number: 1-800-255-3924

SECTION 2 – HAZARDS IDENTIFICATION

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2	H225	Highly flammable liquid and vapor.
Skin Irrit. 2	H315	Causes skin irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

methyl methacrylate

2-ethylhexyl acrylate

Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

Precautionary statements

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT

Not applicable.

vPvB

Not applicable.

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Description: Mixture: consisting of the following components.

Dangerous Components:			
CAS: 80-62-6	methyl methacrylate		
EINECS: 201-297-1	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	50-100%	
Reg.nr.: 01-2119452498-XXXX			
CAS: 103-11-7	2-ethylhexyl acrylate		
EINECS: 203-080-7	Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	2.5-10%	
Reg.nr.: 01-2119453158-37-xxxx			
CAS: 99-97-8	N,N-dimethyl-p-toluidine		
EINECS: 202-805-4	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE 2, H373; Aquatic Chronic 3, H412	≤ 0.5%	
CAS: 38668-48-3	1,1'-(p-tolylimino)dipropan-2-ol		
EINECS: 254-075-1	Acute Tox. 2, H300; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<0.5%	
Reg.nr.: 01-2119980937-17-xxxx			

Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4 – FIRST AID MEASURES

Description of first aid measures

After inhalation

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing

If symptoms persist consult doctor.

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents

CO₂, sand, extinguishing powder. Do not use water.

For safety reasons, unsuitable extinguishing agents

Water with full jet

Special hazards arising from the substance or mixture

No further relevant information available.

Advice for firefighters

Protective equipment

No special measures required.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7 – HANDLING AND STORAGE

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Keep away from heat and direct sunlight.

Prevent formation of aerosols.

Information about fire - and explosion protection

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles

Store in a cool location.

Information about storage in one common storage facility

Not required.

Further information about storage conditions

Keep container tightly sealed.

Store in cool, dry conditions in well-sealed receptacles.

Specific end use(s)

No further relevant information available.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Additional information about design of technical facilities

No further data; see item 7.

Control parameters:

Ingredients with limit values that require monitoring at the workplace:	
80-62-6 methyl methacrylate	
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm

Additional information

The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the Degradation

Material of gloves

PVA gloves

Butyl rubber, BR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection



Tightly sealed goggles

Body protection

Protective work clothing

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid

Color: Colorless

Odor: Characteristic

Odor threshold: 0,5 -1,0 ml/m³ (ppm)

Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: > 101 °C

Flash point: > 10 °C

Ignition temperature: 230 °C

Self-igniting: Product is not self-igniting.

Danger of explosion: Product is not explosive. However, of explosive air/vapor mixtures are possible.

Explosion limits:

Lower: 2.1 Vol %

Upper: 12.5 Vol %

Vapor pressure at 20 °C: 36 hPa

Density at 20 °C: 1.01 g/cm³ (DIN EN ISO 2811-2)

Solubility in / Miscibility with water: Not miscible or difficult to mix.

Viscosity:

Dynamic at 20 °C: 150 mPas (DIN EN ISO 3219)

Other information No further relevant information available.

SECTION 10 – STABILITY AND REACTIVITY

Reactivity

No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided

No decomposition if used according to specifications.

To avoid thermal decomposition do not overheat.

Possibility of hazardous reactions

Exothermic polymerization.

Reacts with acids, alkalis and oxidizing agents.

Conditions to avoid

No further relevant information available.

Incompatible materials

No further relevant information available.

Hazardous decomposition products

Irritant gases/vapors

SECTION 11 – TOXICOLOGICAL INFORMATION

Information on toxicological effects**Acute toxicity**

LD/LC50 values relevant for classification:		
80-62-6 methyl methacrylate		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rat)
Inhalative	LC50/4 h	29.8 mg/l (rat)
103-11-7 2-ethylhexyl acrylate		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	600 mg/l (rat)
99-97-8 N,N-dimethyl-p-toluidine		
Inhalative	LC50/4 h	1.4 mg/l (rat)
38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol		
Oral	LD50	100 mg/kg (rat)

Primary irritant effect:**Skin corrosion/irritation**

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity:	
80-62-6 methyl methacrylate	
EC0	100 mg/l (Pseudomonas putida)
EC50/48 h	69 mg/l (Daphnia (Wasserfloh))
LC50/96 h	> 79 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
103-11-7 2-ethylhexyl acrylate	
EC50/48 h	1.3 mg/l (Daphnia (Wasserfloh))
EC50/72h	1.71 mg/l (Scenedesmus subspicatus (Alge))
LC50/96 h	1.81 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
99-97-8 N,N-dimethyl-p-toluidine	
LC50/96 h	52 mg/l (fish)
38668-48-3 1,1'-(p-tolylimino)dipropan-2-ol	
EC50/48 h	28.8 mg/l (Daphnia (Wasserfloh))

Persistence and degradability

No further relevant information available.

Bio accumulative potential

No further relevant information available.

Mobility in soil

No further relevant information available.

Additional ecological information

General notes

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT

Not applicable.

vPvB

Not applicable.

Other adverse effects

No further relevant information available.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste treatment methods

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 04 09	waste adhesives and sealants containing organic solvents or other dangerous substances

Uncleaned packaging

Recommendation

Disposal must be made according to official regulations.

SECTION 14 – TRANSPORTATION INFORMATION

UN-Number:

ADR, IMDG, IATA

UN1866

UN proper shipping name

ADR

1866 RESIN SOLUTION

IMDG, IATA

RESIN SOLUTION

Transport hazard class(es)

ADR, IMDG, IATA



Class: 3 Flammable liquids.

Label: 3

PACKING GROUP

ADR, IMDG, IATA: II

Environmental hazards

Marine pollutant

Yes

Symbol (fish and tree)

Special marking (ADR)

Symbol (fish and tree)

Special marking (IATA)

Symbol (fish and tree)

Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler)

33

EMS Number

F-E,S-E

Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

Transport/Additional information

ADR

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category

2

Tunnel restriction code

D/E

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation"

UN1866, RESIN SOLUTION, 3, II

SECTION 15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16 – OTHER INFORMATION

Date of Preparation: 11/21/2016

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapor.

H300 Fatal if swallowed.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio accumulative and Toxic

vPvB: very Persistent and very Bio accumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 2: Acute toxicity, Hazard Category 2

Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitization - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3