

### **Armorcoat Fast Part B Hardener**

#### **SECTION 1 – IDENTIFICATION**

GHS product identifier: VSC Armorcoat Fast Part B, Hardener Other means of identification: Epoxy Curing Agent Recommended use of the chemical and restrictions on use: N/A Supplier's details: VANBERG SPECIALIZED COATINGS 10705 COTTONWOOD ST. LENEXA, KS 66215 INFORMATION PHONE NUMBER: 913-599-5939 Emergency phone number: 1-800-255-3924

#### SECTION 2 – HAZARDS IDENTIFICATION

#### Classification of the substance or mixture:

Acute Toxicity – Dermal 4, Skin Corrosion/Irritant 1B, Eye Damage/Irritation 1, Acute Toxicity – Oral 4, Acute Aquatic Toxicity 1

#### GHS label elements:



#### Signal Word: Warning

Hazard Statement: Harmful in contact with skin.

Prevention: Wear protective gloves/protective clothing.

**Response:** If on skin: wash with plenty of soap and water. Call a poison center or doctor/physician if you feel unwell. Immediately flush skin with plenty of water for at least 15 while removing contaminated clothing and shoes. Call a physician if irritation persists. Wash contaminated clothing before reuse.

## g F

#### Signal Word: Danger

Hazard Statement: Causes severe skin burns and eye damage.

**Prevention:** Do not breathe dusts or mists. Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician if irritation persists. Wash contaminated clothing before reuse. If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician. If in eye: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **Storage:** Store locked up.

Disposal: Dispose of in accordance with federal, state, and local regulations.



#### Signal Word: Danger

Hazard Statement: Causes serious eye damage.

Prevention: Wear eye protection/face protection.

**Response:** If in eyes: rinse cautiously with water for several minutes. Remove contact lenses, if Present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

Armorcoat Fast Part B Hardener Page 1 of 6



Signal Word: Warning Hazard Statement: Harmful if swallowed.

**Prevention:** Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. **Response:** If swallowed: Call a poison center or doctor/physician if you feel unwell. Rinse mouth. **Disposal:** Dispose of in accordance with federal, state, and local regulations.



Signal Word: Warning
Hazard Statement: Very toxic to aquatic life.
Prevention: Avoid release into the environment.
Response: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.
Disposal: Dispose of in accordance with federal, state, and local regulations.

Other hazards which do not result in classification NA Hazards Material Information System (United States):

Health	3
Flammability	1
Physical Hazard	1

Hazard Codes: Minimal Hazard, 1=Slight Hazard, 2=Moderate Hazard, 3=Serious Hazard, 4= Severe Hazard

#### SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

#### Mixtures:

Hazardous Components (Chemical Name)	CAS #	Concentration	
Polyoxypropylenediamine	9046-10-0	30-50%	
Aminoethylpiperazine	000140-31-8	10-30%	
Nonylphenol	25154-52-3	40-60%	
2,4,6- tri(dimethylaminomethyl)phenol	90-72-2	5-10%	

#### SECTION 4 – FIRST AID MEASURES

#### Description of necessary first-aid measures:

#### Eye Contact:

Remove contact lenses at once. Immediately flush eyes with large amounts of water or normal saline for at least 30 minutes. Hold eyelids apart while flushing to rinse entire surface of eye and lids with water. Prompt medical attention is essential. **Skin Contact:** 

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician if irritation persists. Wash clothing before reuse. Destroy contaminated shoes.

#### Inhalation:

Remove to fresh air if effects occur. If not breathing, give artificial respiration. Get immediate medical attention.

#### Ingestion:

Do not induce vomiting. If patient is conscious and can swallow, give two glasses of water (16 oz.). Get immediate medical attention. Never give anything by mouth to an unconscious or convulsing person.

#### Most Important symptoms/effects, acute and delayed:

#### **Aggravated Medical Conditions:**

Skin contact may aggravate an existing dermatitis (skin condition). Over exposure to vapor, dust, or mist may aggravate existing respiratory conditions, such as asthma, bronchitis, and inflammatory or fibrotic respiratory disease.

#### Other health effects:

This product contains one or more amines which may produce temporary and reversible hazy or blurred vision. Symptoms disappear when exposure is terminated. May cause liver injury based on animal studies.

#### Indication of immediate medical attention and special treatment needed, if necessary:

Note to physician: May cause tissue destruction leading to stricture. If lavage is performed, suggest endotracheal and/or esophagoscopic control. If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Supportive care. Treatment based on judgment of the physician in response to reactions of the patient. Contact a poison control center for additional treatment information.

#### SECTION 5 – FIRE FIGHTING MEASURES

#### Suitable extinguishing media:

Use water spray, dry chemical, foam, or carbon dioxide. Water or foam may cause frothing. Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for persons attempting to stop the leak.

#### Specific hazards arising from the chemical:

Flash point is 210 °F. Toxic vapors (hydrogen cyanide) may be formed. hazardous combustion products may include intense heat, dense black smoke, carbon monoxide, carbon dioxide, and hydrocarbon fragments.

#### Special protective actions for fire-fighters:

Use a positive pressure self-contained breathing apparatus.

#### SECTION 6 – ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures:

Ventilate the area. Avoid breathing vapor. Use self-contained breathing apparatus or supplied air for large spills or confined areas. **Methods and materials for containment and clean up:** 

Contain spill if possible. Wipe up or absorb on suitable material and pick up with shovels. Do not use sawdust, wood chips, or other cellulosic materials to absorb the spill. Prevent entry into sewers and waterways. Dispose of in accordance with federal, state, and local regulations.

#### SECTION 7 – HANDLING AND STORAGE

#### **Precautions for safe handling:**

Ground all transfer equipment. Take precautionary measures against static discharge. Handle as an industrial chemical.

#### Conditions for safe storage, including any incompatibilities:

Keep container tightly closed when not in use. Practice good caution and personal cleanliness to avoid skin and eye contact. Hold bulk storage under nitrogen blanket. Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures. Copper and alloys of copper should not be used as they are quickly corroded by the product.

#### SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters:** 

N/A

#### Appropriate engineering controls:

N/A

#### Individual protection measures, such as personal protective equipment:

#### **Respiratory Protection:**

Airborne concentrations should be kept to lowest levels possible. Use an approved respirator. Selection of air-purifying or positive-pressure supplied air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus.

#### **Protective Clothing:**

Protective clothing such as uniforms, coveralls, or lab coats must be worn. Launder or dry-clean when soiled. Gloves and goggles resistant to chemicals and petroleum distillates required. When handling large quantities, impervious suits, gloves, and rubber boots must be worn.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Clear, colorless liquid Odor: Ammonia-like odor. Odor threshold: N/A pH: N/A Melting point/freezing point: N/A **Initial boiling point and boiling range:** > 450 °F Flash Point: 210 °F (PMCC) **Evaporation rate: N/A** Flammability (solid, gas): N/A Upper/lower flammability or explosive limits: N/A Vapor pressure: N/A Vapor Density: > 1Relative density (specific gravity): 1.007 **Solubility(ies):** Partially soluble Partition coefficient; n-octanol/water: N/A Auto-ignition temperature: N/A **Decomposition temperature:** N/A Viscosity: N/A

#### SECTION 10 - STABILITY AND REACTIVITY

Reactivity: N/A Chemical stability: Stable under normal conditions of handling. Possibility of hazardous reactions: Will not occur.

# **Conditions to avoid:** Reacts violently with acids. Avoid acid, oxidizing material, halogenated organic compounds, aldehydes, ketones, and acrylates. Results in temperature and/or pressure increase. Avoid exposure to heat, light flame or other sources of ignition.

#### **Incompatible materials:** N/A

#### Hazardous decomposition products:

Toxic levels of ammonia, combustion products of nitrogen, carbon monoxide, carbon dioxide, irritating aldehydes, and ketones may be formed on burning in a limited air supply.

#### SECTION 11 – TOXICOLOGICAL INFORMATION

#### Likely routes of exposure:

N/A

#### Symptoms related to the physical, chemical and toxicological characteristics:

Eye contact:

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. **Skin contact:** 

May cause severe irritation with pain, chemical burns, blister formation, and possible tissue destruction.

#### Inhalation:

May cause respiratory sensitization in susceptible individuals. Severe overexposure may result in difficulty breathing, headache, nausea, vomiting, and drowsiness.

#### **Ingestion:**

Acutely toxic. Causes burning of mouth, throat, and stomach with abdominal and chest pain, nausea, vomiting, diarrhea, thirst, weakness, and collapse. Aspiration may occur during swallowing or vomiting, resulting in lung damage.

Delayed and immediate effects and also chronic effects from short and long term exposure:

N/A

#### Numerical measures of toxicity:

INGREDIENT NAME	CAS #	%	ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
Polyoxypropylenediamine	9046-10-0	30-50	2.885 g/kg (rat)	2.980 g/kg (rabbit)	0/6 deaths (rabbit);7 hrs
Aminoethylpiperazine	000140-31-8	10-30	Not available	900 mg/kg (rabbit)	Not available
Nonylphenol	25154-52-3	40-60	1.600 g/kg (rat)	>200 mg/kg (rabbit)	Not available
2,4,6- tri(dimethylaminomethyl)phenol	90-72-2	5-10	1670 mg/kg (rat)	1242 mg/kg (rabbit)	Not available

#### SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: N/A Persistence and degradability: N/A Bioaccumulative potential: N/A Mobility in soil: N/A Other adverse effects: N/A

#### SECTION 13 – DISPOSAL CONSIDERATIONS

**Disposal methods:** Dispose of in accordance with federal, state, and local regulations.

#### SECTION 14 – TRANPORTATION INFORMATION

UN number: UN 1760 UN proper shipping name: Corrosive liquid, N.O.S., (Polyoxypropylenediamine and Nonylphenol), Marine Pollutant, 8, PG III, UN 1760 Transport hazard class(es): 8 Packing group, if applicable: III Environmental hazards: Marine Pollutant Transport in bulk: N/A Special precautions for user: N/A

#### SECTION 15 – REGULATORY INFORMATION

Safety, health and environmental regulations: Not meant to be all-inclusive. Selected regulations presented. Sara Title III Section 311/312: immediate health hazard. WHMIS Classification: Classes D1B, D2, D2B, E TSCA status: listed on TSCA Inventory OSHA Hazard Comm. Std.: See Section 2

#### Nonylphenol: CA, FL, MA, PA

CA = California Haz. Subst. List; CA65 = California Safe Drinking Water and Toxics Enforcement Act List; CT = Connecticut Tox. Subst. List; FL = Florida Subst. List; IL = Illinois Tox. Subst. List; LA = Louisiana Haz. Subst. List; MA = Massachusetts Subst. List; ME = Maine Haz. Subst. List; MN = Minnesota Haz. Subst. List; NJ = New Jersey Haz. Subst. List; PA = Pennsylvania Haz. Subst. List; RI = Rhode Island Haz. Subst. List.

#### **SECTION 16 – OTHER INFORMATION**

#### Date of Preparation: 05/11/2016

To the best of our knowledge, the information contained herein is accurate. Final determination of the suitability of any material is the sole responsibility of the users. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.