



## Epo-Seal WB-HS Part A

### SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: EPO-SEAL WB-HS PART A  
IDENTIFICATION NUMBER: ES013-2, ES013-5, ES013-2-75  
SUPPLIER/MANUFACTURER: VANBERG SPECIALIZED COATINGS  
10705 COTTONWOOD ST  
LENEXA, KS 66215-2032

EMERGENCY PHONE # 1-800-255-3924  
PREPARER: VSC  
PHONE: 913-599-5939  
PREPARE DATE: OCTOBER 16, 2015

### SECTION 2 – HAZARDS IDENTIFICATION

**GHS Classification:** Specific target organ toxicity – single exposure category 3, Specific target organ toxicity (repeated exposure) category 1

**GHS Label Elements and Precautionary Statements:**

**Label Elements:**



**Hazard Statements:**

Warning: May cause drowsiness or dizziness.

Danger: Causes damage to organs through prolonged or repeated exposure (central nervous system)

**Precautionary statements:**

P102 Keep out of reach of children.

P103 Read label before use

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P272 Contaminated work clothing should not be allowed out of the workplace.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P270 Do not eat, drink or smoke when using this product.

**Response:**

P304 + P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell

**Storage:**

P405 Store locked up.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws

### HMIS Hazard Classification

Health: 2      Flammability: 1      Reactivity: 0      Personal Protective Equipment: G

### Potential Health Effects

**Eyes:** This material can cause eye irritation or redness.

**Skin:** Irritation to the skin can occur but dermal absorption toxicity is low.

**Ingestion:** Ingestion of material can cause nausea and other similar responses.

**Inhalation:** High concentrations of vapor can cause irritation to the respiratory tract, nausea, and dizziness.

### Health hazards (acute and chronic):

Prolonged or repeated exposure may cause asthma and skin sensitization or other allergic responses

**Medical Conditions Generally Aggravated by Exposure:** respiratory conditions or other allergic response.

### Carcinogenicity

OSHA: NO

NTP: NO

IARC: NO

### Additional Carcinogenicity Information:

**No constituents of this products are regulated as carcinogens under OSHA, IARC, or NTP programs.**

**Component CAS# 8052-41-3:** Studies involving petroleum refinery workers indicate that persons with routine exposure to petroleum based constituents may be at an increased risk to the development of benign neoplasms, digestive tract cancer and skin cancer.

## SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT%
Modified Bisphenol A – ECH Based Epoxy Resin	unknown	none	none	none	10-30
Bisphenol A ECH Epoxy Resin	unknown	none	none	none	10-30
Bisphenol A- ECH Epoxy Resin	unknown	none	none	none	10-30
Water	7732-18-5	none	none	none	30-60
Propylene Glycol Monomethyl Ether	107-98-2	100 ppm	100 ppm	150 ppm	10-30
Proprietary Component	unknown	none	none	none	0.1-1
Proprietary Component Considered Trade Secret	unknown	none	none	none	0.1-1
Propylene Glycol Monomethyl Ether	107-98-2	100 ppm	100 ppm	100 ppm	0.1-1
naphtha, petroleum, heavy	64742-82-1	none	none	none	0.1-1
2-Ethyl-1-Hexanol	104-76-7	none	none	none	0.1-1
*Glycol Ether 2-Butoxyethanol	111-76-2	25 ppm	25 ppm	none	1
Proprietary Additive	NJT SRN 800963-5170	none	none	none	0.1-1
Proprietary Additive	NJT SRN 800963-5167	none	none	none	0.1-1
1,2-Propanediol	57-55-6	10 mg/m <sup>3</sup>	none	none	0.1-1
1-Methoxy-2-Propanol	107-98-2	100 ppm	100 ppm	150 ppm	0.1-1
1-Methoxy-2-Propanol Acetate	108-65-6	50 ppm	none	none	0.1-1

\*\*\* Indicates toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

Propylene Glycol Monomethyl Ether CAS # 107-98-2 (ACGIH) STEL=150PPM.

Follow 311b (2) (A) 40 CFR 116,117, Guidelines. Follow TSCA 8 (a) 40 CFR 712, 47 FR 26992 Guidelines

**Note:** Ingredients listed without percentages, the percentages are considered a trade secret.

## SECTION 4 – FIRST AID MEASURES

**Eyes:** Immediately flush with large amounts of water for at least 15 minutes while lifting upper and lower lids. Get immediate medical assistance.

**Skin:** Flush skin with water for at least 15 minutes and remove all contaminated clothing immediately. Get medical attention if reddening or swelling occurs.

**Ingestion:** Do not induce vomiting. Dilute by giving water or milk to drink if victim is conscious. Get medical attention immediately.

**Inhalation:** Remove to fresh air if effects persist and administer oxygen if necessary.

## SECTION 5 – FIRE FIGHTING MEASURES

**Flammable Limits in Air (% by volume):** Upper: not available Lower: not available

**Flash Pt:** 200°F (93°C)

**Method Used:** Set Flash

**Extinguishing Media:**

Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water fog.

**Special Fire Fighting Procedures:**

Toxic fumes will be evolved when this material is involved in a fire. A self-contained breathing apparatus should be available for fire fighters. Cool fire exposed containers with water.

**Unusual Fire and Explosion Hazards:**

No unusual fire hazards known.

## SECTION 6 – RELEASE MEASURES

**Steps to Be Taken in Case Material Is Released or Spilled**

Avoid contact with material. Wear the appropriate safety equipment. Stop spill at source, dyke area to prevent spreading. Pump liquid to salvage tank. Take up remainder with clay or other absorbant and place in disposal containers.

## SECTION 7 – HANDLING AND STORAGE

**Precautions to Be Taken in Handling and Storage:**

Avoid all skin contact. Avoid breathing vapors. Reseal partially used containers. Properly label all containers. Wash with soap and water before eating, drinking, smoking or using toilet facilities. Observe conditions of good industrial hygiene and safe working practices.

**Other Precautions:**

Mixed materials contain the hazards of all the components, therefore, read the SDS of all components to become familiar with all hazards prior to using this product.

## SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

**Respiratory protection:**

NIOSH approved respirator protection required in the absence of proper environmental controls.

**Ventilation:**

Avoid breathing vapors, ventilation must be sufficient to control vapors.

**Protective gloves:**

Impervious gloves, neoprene or rubber.

**Eye protection:**

Splash proof goggles or safety glasses with side shields

**Other protective clothing or equipment:**

Clean body covering clothing as well as apron footwear or other equipment should be used as deemed necessary to avoid contact with the material.

**Work hygienic practices:**

Observe good general hygienic practices.

See Section 3 for occupational exposure limit values.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

**Appearance and Odor:** low viscosity liquid

**Boiling Point or Range:** 212°F (100°C)

**Vapor Density (Air = 1):** N/A  
**Specific Gravity (H<sub>2</sub>O = 1):** 1.0  
**Evaporation Rate:** N/A  
**Solubility in Water:** emulsifiable

**Odor Threshold:** N/A  
**pH:** N/A  
**Melting point/freezing point:** N/A  
**Vapor Pressure:** N/A  
**Auto Ignition Temperature:** N/A  
**Partition Coefficient: n-octanol/water:** N/A  
**Decomposition Temperature:** N/A

## SECTION 10 – STABILITY AND REACTIVITY

**Stability:**

Stable

**Conditions to Avoid (Stability):**

Avoid contact with open flames and all sources of ignitions and sparks.

**Incompatibility (Material to Avoid):**

Can react vigorously with strong oxidizing agents, mineral acids and epoxy resins in uncontrolled amounts.

**Hazardous Decomposition or By-Products:**

CO, CO<sub>2</sub>, NOX

**Hazardous Polymerization:**

Will not occur.

## SECTION 11 – Toxicological Information

No data for the product itself.

**Component data:**

**Component Bisphenol A ECH Epoxy Resin:** Acute oral toxicity LD<sub>50</sub> > 2000 mg/kg, Acute Dermal Toxicity LD<sub>50</sub> > 2000 mg/kg, Acute Inhalation Toxicity LC<sub>50</sub> > 5 mg/l. It is an expected skin sensitizer.

**Component CAS# 107-98-2:** Ingestion LD<sub>50</sub> rat 4016 mg/kg, Dermal LD<sub>50</sub> rabbit >2000 mg/kg, Inhalation LC<sub>50</sub> 6 hr Vapor, rat >25.8 mg/l. May cause eye or skin irritation. May affect Kidney or liver. Has been reported to be toxic to fetus in laboratory animals.

**Component CAS# 64742-82-1:** Acute Oral Toxicity LD<sub>50</sub> >5000 mg/kg; Acute Dermal Toxicity LD<sub>50</sub> rabbit >3000 mg/kg; Acute inhalation Toxicity LC<sub>50</sub> rat >11.6 mg/l; Skin Irritation rabbit – moderate skin irritation.; Eye Irritant – Rabbit.

**Component CAS# 57-55-6:** Acute Oral toxicity LD<sub>50</sub> (rat) = Dose: 20000 mg/kg, Acute dermal toxicity LD<sub>50</sub> (rabbit) dose: 20800 mg/kg, skin irritation – moderate skin irritation (rabbit). Eye irritation – eye irritation (rabbit)

**Component CAS# 108-65-6:** Acute Oral Toxicity LD<sub>50</sub> (rat) = 8532 mg/kg, acute inhalation Toxicity LC<sub>50</sub> (rat) Dose .100ppm exposure time 4h., skin irritation – moderate skin irritation (rabbit), Eye irritation (rabbit – eye irritation).

## SECTION 12 – ECOLOGICAL INFORMATION

No data for the product itself.

**Component data:**

**Component Bisphenol A ECH Epoxy Resin:** Toxicity to fish LC/EC/IC 50 > 100mg/l; Toxicity to algae LC/EC/IC 50 > 100mg/l; Toxicity to Invertebrates LC/EC/IC 50 > 100mg/l

**Component CAS@ 107-98-2:** Bioconcentration potential is low (BCF less than 100). Potential for mobility in soil is high (KOC between 0 and 50). Material is readily biodegradable and is practically non-toxic to aquatic organisms on an acute basis (LC<sub>50</sub>/EC<sub>50</sub>/EL<sub>50</sub>/LL<sub>50</sub> >100mg/l in the most sensitive species tested. LC<sub>50</sub> fathead minnow 96 hr 20800 mg/l, LC<sub>50</sub> water flea 48 hr lethally 23300 mg/l, EbC<sub>50</sub> green algae biomass growth inhibition 7 d >1000 mg/l. Toxicity to microorganisms IC<sub>50</sub> activated sludge > 1000 mg/l

## SECTION 13 – WASTE DISPOSAL

Waste Disposal Method

Dispose of the material in a waste disposal site in accordance with local, state, and federal laws.

**SECTION 14 – TRANSPORT INFORMATION**

**DOT:** Not regulated.  
**IMO/IMDG:** Not regulated.

**SECTION 15 – REGULATORY INFORMATION**

**No data for the product itself.**

**Component data:**

**Component Bisphenol A ECH Epoxy Resin:** All components on the EINECS list, All components on the TSCA list.

**Component CAS# 107-98-2;** on the PA right to know list. Product is on the TSCA list and DSL Canada

**Component CAS# 111-76-2:** Section 313 toxic Chemical. Section 311 hazard category – Chronic, fire, On TSCA list. May contain trace components of benzene, toluene, ethylbenzene and NJTSRN 800963-5170 and contains chemicals known to the state of California to cause cancer and birth defects. All components on the DSL Canada

**Component CAS# 64742-82-1** – on TSCA and on Canada DSL

**Component CAS# 104-76-7:** is on the TSCA and Canada DSL lists.

**Component CAS# 57-55-6:** Listed on TSCA and DSL and is listed on the New Jersey and Pennsylvania right to know lists.

**Component CAS# 108-65-6:** Listed on TSCA and DSL and is listed on the New Jersey and Pennsylvania right to know lists.

**Component Proprietary Additive NJTSRN 800963-5170:** Component is on the TSCA and Canada DSL lists.

**Component Proprietary Additive NJTSRN 800963-5167:** Component is on the TSCA and Canada DSL lists.

**SECTION 16 – OTHER INFORMATION**

**N/A = Not Available**

**See Section 1 for date of preparation**

\*\*\*\*\*

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

**END OF SDS**