



VSC Rust Converter Spray

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

GHS product identifier: VSC Rust Converter Spray

Other means of identification: Rust Converter

Recommended use of the chemical and restrictions on use: N/A

Supplier's details: VANBERG SPECIALIZED COATINGS
10705 COTTONWOOD ST.
LENEXA, KS 66215
INFORMATION PHONE NUMBER: 913-599-5939

Emergency phone number: 1-800-255-3924

SECTION 2 – HAZARDS IDENTIFICATION

CLASSIFICATION:

Flammable Aerosol: Category 1

Liquefied Gas

Eye Irritant: Category 2A

Skin Irritant: Category 2

Specific Target Organ Toxicity (Single Exposure): Category 3

HAZARD STATEMENT(S): DANGER:

Extremely Flammable Aerosol. Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness.

This product contains the following percentage of chemicals of unknown toxicity: 0%

PRECAUTIONARY STATEMENTS:

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention.

Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

SYMBOL:



HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Hazardous Components (Chemical Name)	CAS #	Concentration
2-butoxyethanol	111-76-2	5-10%
Isopropyl Alcohol	67-63-0	5-10%
Propane/n-Butane	68476-86-8	15-40%
Acetone	67-64-1	30-60%
Diethylene Glycol	111-46-6	3-7%
Tannic Acid	1401-55-4	1-5%

Any concentration shown as a range is to protect confidentiality or is due to process variation.

SECTION 4 – FIRST AID MEASURES

First Aid Measures

EYES:

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION:

If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

INHALATION:

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

SKIN:

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

ACUTE HEALTH HAZARDS:

Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Irritation

Oral: abdominal irritation, nausea, vomiting, and diarrhea

CHRONIC HEALTH HAZARDS:

None known

NOTE TO PHYSICIAN:

There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5 – FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Carbon dioxide, foam, and water fog.

UNSUITABLE EXTINGUISHING MEDIA:

Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS:

Oxides of carbon

SECTION 6 – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT:

Refer to section VIII for proper Personal Protective Equipment.

SPILL:

Use non-combustible material like vermiculite, sand or earth on spill sweep to clean. Dispose in accordance with local, state and federal laws. Small releases may be wiped up with wiping material.

WASTE DISPOSAL:

Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS:

Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION 7 – HANDLING AND STORAGE

HANDLING AND STORAGE:

Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

OTHER PRECAUTIONS:

Keep out of the reach of children.

INCOMPATIBILITY:

Concentrated nitric & sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, plastics, rubber, coatings

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters:

Hazardous Components (Chemical Name)	OSHA PEL	ACGIH TLV
2-Butoxyethanol	50 ppm	20 ppm
Isopropyl Alcohol	400 ppm	200 ppm
Propane/n-Butane	n/a	1000 ppm
Acetone	1000 ppm	500 ppm
Diethylene Glycol	Not Established	Not Established
Tannic Acid	Not Established	Not Established

ENGINEERING CONTROLS / VENTILATION:

Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION:

Not required with normal use.

PERSONAL PROTECTIVE EQUIPMENT:

Safety glasses and chemical resistant gloves.

ADDITIONAL MEASURES:

Wash hands thoroughly after handling.

EXPOSURE GUIDELINES:

Extremely Flammable

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, Brown Aerosol

ODOR: Solvent

ODOR THRESHOLD: N/D

BOILING POINT: > 150°F (66°C)

FREEZING POINT: N/D

FLAMMABILITY: Extremely Flammable Aerosol

FLASH POINT: 65°F (18°C)

AUTOIGNITION TEMPERATURE: N/D

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT:N/D
VAPOR PRESSURE (mm Hg): 77.3 @ 77°F (25°C)
VAPOR DENSITY (AIR=1): > 1 @ 77°F (25°C)
EVAPORATION RATE: > 1
SPECIFIC GRAVITY (H2O=1): .85 @ 77°F (25°C)
pH: 1.9
SOLUBILITY IN WATER: Non-soluble
PARTITION COEFFICIENT: n-OCTANOL/WATER (KOW): N/D
VOLATILE ORGANIC COMPOUNDS (VOC): 51%
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION 10 – STABILITY AND REACTIVITY

REACTIVITY:

None Known

CHEMICAL STABILITY:

Stable

CONDITIONS TO AVOID:

Extremes of hot and cold.

INCOMPATIBILITY:

Concentrated nitric & sulfuric acid mixtures, oxidizing materials, chloroform, alkalis, chlorine compounds, acids, plastics, rubber, coatings

HAZARDOUS DECOMPOSITION OR BY-PRODUCT:

Oxides of carbon

POSSIBLE HAZARDOUS REACTIONS:

None Known

SECTION 11 – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: 2-Butoxyethanol (111-76-2) LD50 (Oral, Rat) 320 mg/kg; LC50(Inhalation, Mice, 4hr) 700 ppm; LD50(Dermal, Rabbit) 440 mg/kg Acetone(67-64-1) LD50(Oral, Rat) 5800 mg/kg; LD50(Oral, Mouse) 3000 mg/kg; LD50 (Oral, Rabbit) 5340 mg/kg; LC50 (Inhalation, Rat, 8hr) 50100 mg/m3; LC50 (Inhalation, Mouse, 4hr) 44,000 mg/m3 Diethylene Glycol (DEG) (111-46-5) LD50 (Oral, Rat) 25,300 mg/kg; LD50(Oral, Human) 1,000 mg/kg; LD50 (Dermal, Rabbit) 12,500 mg/kg; LC50 (Inhalation, Rat) > 1,172 ppm Propane/n-Butane (68476-86-8) LC50(Inhalation, Rat, 4hr) 685 mg/m3

ROUTES OF ENTRY:

Eyes, Ingestion, Inhalation, Skin

EYES:

Redness, irritation, causes temporary corneal opacity.

INGESTION:

Nausea.

INHALATION:

Will cause dizziness, anesthesia and possibly death if breathed directly.

SKIN:

May cause burns.

MEDICAL CONDITION AGGRAVATED:

None known

ACUTE HEALTH HAZARDS:

Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Irritation

Oral: abdominal irritation, nausea, vomiting, and diarrhea

CHRONIC HEALTH HAZARDS:

None known

CARCINOGENICITY: OSHA:

No

ACGIH:

No

NTP:

No

IARC:

No

OTHER:

No

SECTION 12 – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: 2-Butoxyethanol (111-76-2) Toxic to aquatic life only in high concentrations, lethal concentrations not available. Acetone(67-64-1) LC50 (Trout, 96hr) 5540 mg/L; LC50 (Bluegill, 96hr) 8300 mg/L; LC50 (Fathead Minnow, 96hr) 7500 mg/L Diethylene Glycol (DEG) (111-46-5) LC50 (Bluegill Sunfish) > 1000 mg/L Isopropyl Alcohol (67-63 0) LC50 (Fathead Minnow, 96 hrs) 9640 mg/L

BIODEGRADABILITY:

Component or components of this product are not biodegradable.

BIOACCUMULATION:

This product is not expected to bioaccumulate.

SOIL MOBILITY:

This product is mobile in soil.

OTHER ECOLOGICAL HAZARDS:

None Known

SECTION 13 – DISPOSAL CONSIDERATIONS**Waste Disposal Method**

Dispose of material in accordance with all Federal, State and local regulations. Local regulations may be more stringent than Federal or State. Avoid discharge to sewers or waterways.

RCRA STATUS:

Waste likely considered hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261)

SECTION 14 – TRANSPORTATION INFORMATION**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.**HAZARD CLASS/DIVISION:** 2.1**UN/NA NUMBER:** UN 1950**PACKAGING GROUP:** N/A**AIR SHIPMENT****PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.**HAZARD CLASS/DIVISION:** 2.1**UN/NA NUMBER:** UN 1950**PACKAGING GROUP:** N/A**SHIPPING BY WATER:** VESSEL (IMO/IMDG)**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.**HAZARD CLASS/DIVISION:** 2.1**UN/NA NUMBER:** UN 1950**PACKAGING GROUP:** N/A**ENVIRONMENTAL HAZARDS WATER:** N/A**SECTION 15 – REGULATORY INFORMATION****TSCA STATUS:**

All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):

Fire Hazard

Acetone (67-64-1) Reportable Quantity = 5,000 lbs

SARA 311/312 HAZARD CATEGORIES:

Fire Hazard

SARA 313 REPORTABLE INGREDIENTS:

2-Butoxyethanol (111-76-2)

CLEAN WATER ACT:

None

STATE REGULATIONS:

This product contains no known chemicals regulated by California's proposition 65. 2-Butoxyethanol(111-76-2) RTK: NJ, MA, PA

INTERNATIONAL REGULATIONS:

2-Butoxyethanol (111-76-2) Europe (EINECS), Japan (ENCS), Australia (AICS), WHMIS (Canada), DSCL (EEC), NDSL, Korea (ECL), Philippines (PICCS), New Zealand (NZIOC), China (IECS). Acetone(67-64-1) Australia, China, Europe (EINECS), Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSCL (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice.

NFPA HEALTH: 2

HMIS HEALTH: 2

NFPA FLAMMABILITY: 4

HMIS FLAMMABILITY: 4

NFPA REACTIVITY: 1

HMIS REACTIVITY: 1

NFPA OTHER: None

HMIS PROTECTION: B

SECTION 16 – OTHER INFORMATION

Date of Preparation: 05/12/2016

To the best of our knowledge, the information contained herein is accurate. Final determination of the suitability of any material is the sole responsibility of the users. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.