



686 S. Adams St. | Kansas City, KS 66105 | (913) 321-9000 | www.versaflex.com

Selection and Specification Data

| | | |
|--|--|-----------------|
| <p>Description</p> <p>VersaFlex Dzolv is a water soluble, organic solvent containing no aromatics or petroleum distillates. Dzolv is designed to provide maximum stripping effectiveness while incorporating a high flash point and low toxicity. Dzolv replaces most industrial solvents such as chlorinated hydrocarbons (methylene chloride, carbon tetrachloride and 1,1,1 trichloroethane) when used on cured polymers.</p> <p>Ideal for Stripping</p> <ul style="list-style-type: none"> • Polyurea • Polyurethane • Epoxies • Polyester resins. <p>Advantages:</p> <ul style="list-style-type: none"> • VOC level acceptable to SCAQMD region • Non toxic • Easy to apply • Flash point >200°F • Low odor • Indefinite shelf life • Will not cause hazardous polymerization • Low evaporation rate • Not R.C.R.A or DOT regulated. Dzolv's water solubility allows for safe use. | Physical Properties (Typical) Independent Testing | |
| | Color | Clear liquid |
| | Specific Gravity @ 25°C | 1.08 @ 77°F |
| | Flash Point | >200°F |
| | Odor | Mild sweet odor |
| Preparation and Application | | |
| <p>Apply Dzolv liberally or employ baths where possible for stationary stripping. May be applied by brush. May be used to strip various gun parts—Consult Versaflex. <u>NOT recommended for flushing plural component machines.</u></p> | | |
| Safety | | |
| <p>Safety - Review SDS at www.versaflex.com.</p> <ul style="list-style-type: none"> • Wear Long sleeve overalls or disposable Tyvex suit • Rubber gloves • Protective eye wear • Rubber or leather boots • Respirator • Do not use near high heat or open flame • Do not take internally • Keep out of reach of children | | |

Precautions

| | |
|--|--|
| <p>This product contains Volatile Organic Compounds (VOC's) which may be released during and for some period after installation producing odors and affecting air quality. To avoid possible contamination of sensitive substances and for protection of human health, ensure proper air ventilation of work areas until odors completely dissipate.</p> | <p>Reacts violently with strong acids or bases.</p> |
|--|--|



Packaging, Handling, and Storage

Packaging

Available in **1, 5, and 55-gallon** containers.

Shelf Life

One year from shipment date, in original, unopened factory containers.

Storage Temperature & Humidity

Under normal storage conditions of 70°F to 95°F (21° - 35°C).

Warranty

Limited Warranty. Company warrants its goods to be free of manufacturing defects. Goods manufactured by Company will comply with all applicable federal, state and local laws and regulations. Company makes no warranty as to any parts or equipment manufactured by others. Customer shall look solely and only to the manufacturer of such parts or equipment with respect to any warranty claims. Company hereby assigns to Customer the original manufacturer’s warranties to all such equipment and parts, to the full extent permitted. THE AFORESAID IS THE EXCLUSIVE WARRANTY AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. SPECIFICALLY, THERE ARE NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.

Limitation of Liability. COMPANY’S LIABILITY FOR DEFECTIVE OR NON-CONFORMING GOODS SHALL BE LIMITED TO, AND SHALL IN NO EVENT EXCEED, THE AMOUNT PAID BY CUSTOMER FOR SUCH DEFECTIVE OR NON-CONFORMING GOODS. UNDER NO CIRCUMSTANCES SHALL COMPANY BE LIABLE FOR ANY SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR FOR LOST PROFITS. In no event may any claim by Customer arising from or relating to any sale of any goods or services referenced herein be brought more than one year after the date of delivery of such Goods.