



VersaFlush™

Flushing Agent
Technical Data Sheet

686 S. Adams St. | Kansas City, KS 66105 | (913) 321-9000 | www.versaflex.com

Selection and Specification Data

Description

VersaFlex VersaFlush™ is a unique flushing solvent to be used to flush and remove the components of a polyurea or polyurethane plural component system from application equipment. VersaFlush replaces other solvents such as DOP, DINP, methylene chloride, acetone, MEK, and 1,1,1 trichloroethane. VersaFlush may be used for extended periods in application equipment and may reduce disposal costs.

Effective with

- Liquid components of Polyurea coatings
- Liquid components of Polyurethane Spray foam, or coatings
- Liquid components of Polyaspartic coatings

Advantages

- VOC level acceptable to SCAQMD region
- Non toxic & non-chlorinated
- Non carcinogenic & non-ozone depleting
- Non-flammable
- Easy to use
- Flash point >200°F
- Low odor
- Indefinite shelf life
- Will not cause hazardous polymerization
- Low evaporation rate

Physical Properties (Typical) Independent Testing

Color	Clear liquid
Specific Gravity @ 25°C	1.1 @ 77°F
Flash Point	>200°F
Odor	Typical solvent

Preparation and Application

Utilize VersaFlush in the same manner that would be used for spraying. Mild heating of the solvent will produce faster results. VersaFlush may be left in the feed lines and hoses once used or until next time equipment is used.

Safety

Safety - Review SDS at www.versaflex.com.

- Wear Long sleeve overalls or disposable Tyvex suit
- Rubber gloves
- Protective eye wear
- Rubber or leather boots
- Respirator
- Do not use near high heat or open flame
- Do not take internally
- Keep out of reach of children

Packaging, Handling, and Storage

Packaging

Available in **1,5**, and **55 gallon** containers.

Shelf Life

One year from shipment date, in original, unopened factory containers.

Storage Temperature & Humidity

Under normal storage conditions of 70°F to 95°F (21° - 35°C).

Precautions

This product contains Volatile Organic Compounds (VOC's) which may be released during and for some period after installation producing odors and affecting air quality. To avoid possible contamination of sensitive substances and for protection of human health, ensure proper air ventilation of work areas until odors completely dissipate.



VersaFlush™
Flushing Agent
Technical Data Sheet

Warranty

Limited Warranty. Company warrants its goods to be free of manufacturing defects. Goods manufactured by Company will comply with all applicable federal, state and local laws and regulations. Company makes no warranty as to any parts or equipment manufactured by others. Customer shall look solely and only to the manufacturer of such parts or equipment with respect to any warranty claims. Company hereby assigns to Customer the original manufacturer's warranties to all such equipment and parts, to the full extent permitted. THE AFORESAID IS THE EXCLUSIVE WARRANTY AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED. SPECIFICALLY, THERE ARE NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.

Limitation of Liability. COMPANY'S LIABILITY FOR DEFECTIVE OR NON-CONFORMING GOODS SHALL BE LIMITED TO, AND SHALL IN NO EVENT EXCEED, THE AMOUNT PAID BY CUSTOMER FOR SUCH DEFECTIVE OR NON-CONFORMING GOODS. UNDER NO CIRCUMSTANCES SHALL COMPANY BE LIABLE FOR ANY SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR FOR LOST PROFITS. In no event may any claim by Customer arising from or relating to any sale of any goods or services referenced herein be brought more than one year after the date of delivery of such Goods.