

1. Product and Company Identification

Product Name: GelFlex S (B-side)

VersaFlex 686 South Adams Street Kansas City, KS 66105

www.versaflex.com

Company Phone: (913) 321-9000 Company Toll Free: (800) 321-0906

CHEMTREC 24 hour Emergency USA: (800) 424-9300 CHEMTREC 24 hour International: (703) 527-3887

Product Use: Primer / Sealer / Coating / Lining Not recommended for: Non Professional Use

2. Hazards Identification

Signal Word: Danger





GHS Ratings:

Skin sensitizer 1 Skin sensitizer.

Mutagen 1B Known to produce heritable mutations in human germ cells

Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell

mutagenicity.

Carcinogen 1A Known Human Carcinogen Based on human evidence.

GHS Hazards

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

GHS Precautions

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.
P321 Specific treatment (see Section 4 of the SDS).
P363 Wash contaminated clothing before reuse.
P302+P352 IF ON SKIN: Wash with soap and water.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container according to Section 13 of the SDS.

3. Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Trade Secret	N/A	40 - 50%
Titanium Dioxide	13463-67-7	10 - 20%
Aspartic Acid Ester	168253-59-6	10 - 20%
Crystalline Silica, Quartz	14808-60-7	5 - 10%
Amorphous Silicon Dioxide	7631-86-9	1 - 5%
Aluminum Oxide	1344-28-1	1 - 5%
N-Butyl-2-(1-ethylpentyl)-1,3-oxazolidine	165101-57-5	1 - 5%
Amorphous Hydrophobic Fumed Silica	67762-90-7	1 - 5%
Mica	12001-26-2	1 - 5%
Trade Secret	N/A	1 - 5%
Fumaric Acid Diester	623-91-6	1 - 5%
Solvent naphtha, petroleum, light aromatic	64742-95-6	0.1 - 1%

4. First Aid Measures

Inhalation: Remove to fresh air if effects occur. Consult a physician.

Eye Contact: Flush with large quantities of water for at least 15 minutes. Consult a physician.

Skin Contact: Wash thoroughly with soap and flowing water.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire Fighting Measures

Flash Point: >105 C (>221 F)

Flammable Properties: Product is not considered a fire hazard, but will burn if ignited.

NFPA Flammability Class: Class III A liquids are combustible liquids that have a flash point ≥ 140 deg F (60 deg C), but < 200 deg F (93 deg C). Class III B liquids are combustible liquids that have a flash point >200 deg F.

Suitable Extinguishing Media: Carbon dioxide, dry chemical, water fog or fine spray. Alcohol resistant foams are preferred, general purpose synthetic foams or protein foams may function, but will not be as effective.

Unsuitable Extinguishing Media: Do not use direct water stream, as it may spread fire.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides and other unidentified toxic and/or irritating compounds.

Fire Fighting: Stay upwind and keep people away. Isolate fire and deny unnecessary entry. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out. Contain fire water run-off if possible, as it may cause environmental damage. Review section 6 and section 12 of this SDS.

Protection of Firefighters: Wear positive pressure self-contained breathing apparatus (SCBA) and approved protective clothing (helmet, coat, trousers, boots and gloves). If contact is likely, use full chemical resistant fire fighting clothing with SCBA.

6. Accidental Release Measures

Personal Precautions: Put on appropriate personal protective equipment (see section 8).

Environmental Precautions: Prevent spilled material from contact with soil, drains and sewers.

Methods for Containment: Contain by diking with sand, earth or other suitable material.

SDS for: GelFlex S (B-side) Page 2 of 8

Methods for Clean-up: Absorb spill with an inert material, use non-sparking tools to place into labeled waste container for disposal.

7. Handling and Storage

Handling: Wear appropriate personal protective equipment (see section 8). Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Do not ingest. Avoid prolonged or repeated contact with skin. May cause allergic skin reaction, persons with a history of skin sensitization should not be employed in any process in which this product is used. Wash thoroughly with soap and water after handling. Do not handle or store near flame, heat or strong oxidants. Keep away from sources of ignition and hot metal surfaces.

Storage: Store original unopened containers in a sheltered area between 60°F and 80°F (15°C and 27°C) at atmospheric pressure. Do not store in direct sunlight. Keep containers closed when not in use.

8. Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Trade Secret N/A	Not Established	Not Established	Not Established
Titanium Dioxide 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	Not Established
Aspartic Acid Ester 168253-59-6	Not Established	Not Established	Not Established
Crystalline Silica, Quartz 14808-60-7	PELs - (30)/(%SiO2 + 2) mg/m3 TWA, total dust PELs - (250)/(%SiO2 + 5) mppcf TWA, respirable fraction PELs - (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction	0.025 mg/m3 TWA (respirable fraction)	NIOSH: 0.05 mg/m3 TWA (respirable dust)
Amorphous Silicon Dioxide 7631-86-9	Not Established	Not Established	NIOSH: 6 mg/m3 TWA
Aluminum Oxide 1344-28-1	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	Not Established	Not Established
N-Butyl-2-(1-ethylpentyl)-1,3- oxazolidine 165101-57-5	Not Established	Not Established	Not Established
Amorphous Hydrophobic Fumed Silica 67762-90-7	Not Established	Not Established	Not Established
Mica 12001-26-2	Not Established	3 mg/m3 TWA (respirable fraction)	NIOSH: 3 mg/m3 TWA (containing <1% Quartz, respirable dust)
Trade Secret N/A	Not Established	Not Established	Not Established
Fumaric Acid Diester 623-91-6	Not Established	Not Established	Not Established
Solvent naphtha, petroleum, light aromatic 64742-95-6	Not Established	Not Established	Not Established

Engineering Controls: General mechanical ventilation is sufficient for most conditions. Control airborne levels below the exposure guidelines, if established.

Local exhaust ventilation may be necessary for some operations.

General Hygiene Considerations: Wash thoroughly after handling and before eating, drinking or smoking.

Eye/face Protection: Use chemical safety glasses, splash-proof eye goggles or goggles with full faceshield. Skin Protection: Use nitrile or other impermeable chemical resistant gloves to prevent skin irritation. If potential for skin contact is present, wear impervious, long-sleeved, body covering clothing and rubber boots.

Respiratory Protection: Respiratory protection should not be needed. If exposure may or does exceed occupational exposure limits, respiratory irritation is experienced, or during spray application, use a properly fitted MSHA/NIOSH approved respirator fitted with organic vapor cartridges. In addition, spray application may require the use of paint pre-filters. If the respirator is the sole means of protection, use a full-face supplied air respirator. If sanding or grinding on cured material, use above respirator fitted with HEPA filters or a dust mask.

Contaminated Gear: Remove contaminated clothing and shoes while washing. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

9. Physical and Chemical Properties

Appearance Product color varies

Odor Threshold No data found

pH No data found

Boiling Point 214°C

Flash Point 221°F, 105°C

Flammability (solid, gas) No data found

Vapor Pressure No data found

Specific Gravity 1.2 - 1.4

Partition Coefficient No data found (n-octanol/water)

Decomposition Temperature No data found

Lbs VOC/Gallon Less Water 0.0

Odor Ammonia-like

Physical State Liquid

Melting/Freezing Point No data found

Boiling Range No data found

Evaporation Rate No data found

LEL/UEL No data found

Vapor Density No data found

Solubility in Water No data found

Autoignition Temperature No data found

Viscosity No data found

10. Stability and Reactivity

Chemical Stability: Stable under recommended storage conditions (see Section 7).

Conditions to Avoid: Elevated temperatures may cause product to decompose.

Incompatible Materials: Strong acids, bases, or oxidizing agents. Avoid unintended contact with isocyanates and/or epoxies.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides and other unidentified toxic and/or irritating compounds.

Hazardous polymerization will not occur.

11. Toxicological Information

Mixture Toxicity

Component Toxicity

Toxicological information on this product or its components appear in this section when such data is available.

Likely Routes of Exposure:

No data found

Target Organs

May cause damage to the following organs:

Eyes Skin Respiratory System

Effects of Overexposure

Harmful if inhaled.

Carcinogenicity: Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2b) through inhalation (not ingestion), based on lifetime inhalation studies of rats. The IARC's findings were consistent with the massive accumulation of fine dust particles in the rat's lung (which overwhelm the natural lung clearance mechanisms, causing lung overloading) and consequential pulmonary overload and inflammation that causes lung

SDS for: GelFlex S (B-side) Page 4 of 8

cancer. In further studies, these tumors were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. Epidemiology studies on more than 20,000 workers do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. If present in this product, the titanium dioxide is in a "wet out" form and does not pose an inhalation hazard.

Carcinogenicity: This product may contain carbon black, a substance that has been listed by OSHA as a carcinogen to humans when inhaled. If present in this product, it is pre-dispersed in a liquid and not available as a dust. Under normal use conditions it would not be considered a hazard. IARC characterized carbon black as a possible human carcinogen (Group 2B) and concluded that there is sufficient evidence in experimental animals for the carcinogenicity of inhaled carbon black dust and inadequate evidence of carcinogenicity in humans. The IARC's findings were consistent with the massive accumulation of fine dust particles in the lung which overwhelm the natural lung clearance mechanisms, known as "lung overload" phenomenon, rather than from a specific chemical effect from the carbon black in the lung. NIOSH recommends that only carbon blacks with a PAH level greater than 0.1% be considered potential occupational carcinogens.

Carcinogenicity: This product may contain crystalline silica (quartz), a substance that has been classified as carcinogenic to humans when inhaled. If present in this product, it is pre-dispersed and not available as a dust. Under normal use conditions it would not be considered a hazard.

<u>CAS Number</u> 13463-67-7	<u>Description</u> Titanium Dioxide	<u>% Weight</u> 10 - 20%	Carcinogen Rating Titanium Dioxide: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
14808-60-7	Crystalline Silica, Quartz	5 - 10%	Crystalline Silica, Quartz: NIOSH: potential occupational carcinogen IARC: Human carcinogen OSHA: listed
64742-95-6	Solvent naphtha, petroleum, light aromatic	0.1 - 1%	Solvent naphtha, petroleum, light aromatic: EU REACH: Present (P)

12. Ecological Information

Component Ecotoxicity

Amorphous Silicon Dioxide 96 Hr LC50 Brachydanio rerio: 5000 mg/L [static]

48 Hr EC50 Ceriodaphnia dubia: 7600 mg/L

72 Hr EC50 Pseudokirchneriella subcapitata: 440 mg/L

Solvent naphtha, petroleum, light 96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L

aromatic 48 Hr EC50 Daphnia magna: 6.14 mg/L

13. Disposal Considerations

Waste Disposal Methods: Dispose of in accordance with federal, state and local regulations. The preferred method for disposal of uncontaminated product is by recycling, reclaiming, incineration or other thermal destruction device using a licensed and permitted waste disposal contractor.

14. Transport Information

Agency Proper Shipping Name UN Number Packing Group Hazard Class

DOT Not Regulated ICAO/IATA Not Regulated IMDG Not Regulated TDG Not Regulated

15. Regulatory Information

USA Federal: This SDS has been prepared in compliance with the Occupational Safety and Health Act (OSHA) Hazard Communication Standard (29 CFR 1910.1200). This product is considered to be a hazardous chemical under that standard. The specific chemical identity and/or exact percentage of any proprietary ingredient(s) may be withheld as a trade secret, pursuant to the standard.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): To the best of our knowledge, this product contains the following chemicals which are known to the State of California to cause cancer, developmental or reproductive toxicity at levels which require warning under this statute:

```
14808-60-7 Crystalline Silica, Quartz 5 to 10 % Carcinogen 13463-67-7 Titanium Dioxide 10 to 20 % Carcinogen
```

USA Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) - section 103 Hazardous Substances Reportable Quantities (RQs): To the best of our knowledge, this product contains the following chemicals which are listed in 40 CFR 302.4:

- None

Massachusetts Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

```
12001-26-2 Mica 1 to 5 %
1344-28-1 Aluminum Oxide 1 to 5 %
7631-86-9 Amorphous Silicon Dioxide 1 to 5 %
14808-60-7 Crystalline Silica, Quartz 5 to 10 %
13463-67-7 Titanium Dioxide 10 to 20 %
```

New Jersey Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

```
12001-26-2 Mica 1 to 5 %
1344-28-1 Aluminum Oxide 1 to 5 %
7631-86-9 Amorphous Silicon Dioxide 1 to 5 %
14808-60-7 Crystalline Silica, Quartz 5 to 10 %
13463-67-7 Titanium Dioxide 10 to 20 %
```

Pennsylvania Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

```
12001-26-2 Mica 1 to 5 %
1344-28-1 Aluminum Oxide 1 to 5 %
7631-86-9 Amorphous Silicon Dioxide 1 to 5 %
14808-60-7 Crystalline Silica, Quartz 5 to 10 %
13463-67-7 Titanium Dioxide 10 to 20 %
```

USA Resource Conservation and Recovery Act (40 CFR 261): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

USA Superfund Amendments and Reauthorization Act (SARA) of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 313 Toxic Release Inventory (TRI) Form R: To the best of our knowledge, this product contains the following chemicals which are listed in 40 CFR 372.65:

- None

USA Superfund Amendments and Reauthorization Act (SARA) of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 302 Extremely Hazardous Substances Threshold Planning Quantities (TPQs): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

USA Toxic Substances Control Act (TSCA) - section 12(b): To the best of our knowledge, this product contains the following chemicals above the de minimus concentration(s) which requires notification to the Environmental Protection Agency (EPA) per 40 CFR 707, subpart D, if any person intends to export:

Country	Regulation	All Components Listed
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Canada Domestic Substance List	No
Canada	Canada Non-Domestic Substances List (NDSL)	No
China	China Inventory of Existing Chemical Substances	No
EU	EU REACH List of Registered Intermediates	No
EU	EU REACH List of Pre-Registered Substances	Yes
EU	EU REACH List of Registered Substances	No
Japan	Japanese Existing and New Chemical Substances List	No
South Korea	South Korea Existing Chemicals Inventory	No
Philippines	Philippines Inventory of Chemicals and Chemical	No
USA	USA TSCA Inventory list section 8(b)	Yes

- None

16. Other Information

Legend

ACGIH American Conference of Governmental Industrial Hygienists, Inc.

ADR/RID European Agreement for transport of dangerous goods by road (ADR) and by rail (RID)

CAS No. Chemical Abstract Service Registry Number

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act, AKA "Superfund"

DOT Department of Transportation (USA)

HCS OSHA Hazard Communication Standard (29 CFR 1910.1200)

IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 ICAO International Civil Aviation Organization
 IMO International Maritime Organization
 IMDG International Maritime Dangerous Goods
 MSHA Mine Safety and Health Administration

N.A. Not Applicable
N.D. Not Determined
N.E. Not Established

NFPA National Fire Protection Association

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration (USA)

PEL Permissible Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986 (40 CFR)
STEL Short Term Exposure Limit (15 minute Time Weighted Average)

TDG Canada Transport of Dangerous Goods regulations

TLV Threshold Limit Value TWA Time Weighted Average

WHMIS Canada Workplace Hazardous Materials Information System

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating Legend


* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH



Disclaimer

VERSAFLEX MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO ANY INFORMATION PRESENTED HEREIN, ALL OF WHICH IS PROVIDED "AS IS". TO THE MAXIMUM EXTENT PERMITTED BY LAW, VERSAFLEX EXPRESSLY EXCLUDES ALL WARRANTIES, OBLIGATIONS, REPRESENTATIONS, LIABILITIES, TERMS AND CONDITIONS (WHETHER THEY ARE EXPRESS OR IMPLIED, OR ARISE IN CONTRACT, STATUTE, OR OTHERWISE, AND IRRESPECTIVE OF THE NEGLIGENCE OF VERSAFLEX, ITS EMPLOYEES OR AGENTS) IN CONNECTION WITH THE INFORMATION PRESENTED HEREIN. VERSAFLEX MAKES NO REPRESENTATIONS OR WARRANTIES AS TO MERCHANTABILITY, FITNESS FOR PURPOSE, NONINFRINGEMENT OR CONFORMITY WITH DESCRIPTION OR SAMPLE.

Reviewer Revision

Date Prepared: 4/22/2020