

1. Product and Company Identification

Product Name: VersaRoof S (B-Side)

The VersaFlex Companies
686 South Adams Street
Kansas City, KS 66105

www.versaflex.com

Company Phone: (913) 321-9000
Company Toll Free: (800) 321-0906

CHEMTREC 24 hour Emergency USA: (800) 424-9300
CHEMTREC 24 hour International: (703) 527-3887

Product Use: Primer / Sealer / Coating / Lining / Foam
Not recommended for: Non Professional Use

2. Hazards Identification

Signal Word: Warning



GHS Ratings:

Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation.
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days.
Skin sensitizer	1	Skin sensitizer.
Aquatic toxicity	C3	Acute toxicity > 10.0 but ≤ 100.0 mg/l and lack of rapid degradability and $\log Kow \geq 4$ unless $BCF < 500$ and unless chronic toxicity > 1 mg/l

GHS Hazards

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

GHS Precautions

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P321	Specific treatment (see Section 4 of the SDS).
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with soap and water.

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container according to Section 13 of the SDS.

3. Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Polyoxyalkyleneamine	9046-10-0	30 - 60%
Diethyltoluenediamine	68479-98-1	10 - 30%
Glycerine, propoxylated aminated	64852-22-8	7 - 13%
Trade Secret		7 - 13%
Titanium dioxide	13463-67-7	0 - 5%
Polyether Polyol	25791-96-2	1 - 5%
Carbon Black	1333-86-4	0 - 1%

4. First Aid Measures

Inhalation: Remove to fresh air if effects occur. Consult a physician.

Eye Contact: Flush with large quantities of water for at least 15 minutes. Consult a physician.

Skin Contact: Wash thoroughly with soap and flowing water.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire Fighting Measures

Flash Point: >100 C (>212 F)

Flammable Properties: Product is not considered a fire hazard, but will burn if ignited.

NFPA Flammability Class: Class III A liquids are combustible liquids that have a flash point \geq 140 deg F (60 deg C), but < 200 deg F (93 deg C). Class III B liquids are combustible liquids that have a flash point \geq 200 deg F.

Suitable Extinguishing Media: Carbon dioxide, dry chemical, water fog or fine spray. Alcohol resistant foams are preferred, general purpose synthetic foams or protein foams may function, but will not be as effective.

Unsuitable Extinguishing Media: Do not use direct water stream, as it may spread fire.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides and other unidentified toxic and/or irritating compounds.

Fire Fighting: Stay upwind and keep people away. Isolate fire and deny unnecessary entry. Keep out of low areas where gases (fumes) can accumulate. Water is not recommended, but may be applied in large quantities as a fine spray when other extinguishing agents are not available. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out. Contain fire water run-off if possible, as it may cause environmental damage. Review section 6 and section 12 of this SDS.

Protection of Firefighters: Wear positive pressure self-contained breathing apparatus (SCBA) and approved protective clothing (helmet, coat, trousers, boots and gloves). If contact is likely, use full chemical resistant fire fighting clothing with SCBA.

6. Accidental Release Measures

Personal Precautions: Put on appropriate personal protective equipment (see section 8).

Environmental Precautions: Prevent spilled material from contact with soil, drains and sewers.

Methods for Containment: Contain by diking with sand, earth or other suitable material.

Methods for Clean-up: Absorb spill with an inert material, use non-sparking tools to place into labeled waste container for disposal.

7. Handling and Storage

Handling: Wear appropriate personal protective equipment (see section 8). Avoid contact with skin, eyes or clothing. Do not breathe vapor or mist. Do not ingest. Avoid prolonged or repeated contact with skin. May cause allergic skin reaction, persons with a history of skin sensitization should not be employed in any process in which this product is used. Wash thoroughly with soap and water after handling. Do not handle or store near flame, heat or strong oxidants. Keep away from sources of ignition and hot metal surfaces.

Storage: Store original unopened containers in a sheltered area between 60°F and 80°F (15°C and 27°C) at atmospheric pressure. Do not store in direct sunlight. Keep containers closed when not in use.

8. Exposure Controls / Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Polyoxyalkyleneamine 9046-10-0	Not Established	Not Established	Not Established
Diethyltoluenediamine 68479-98-1	Not Established	Not Established	Not Established
Glycerine, propoxylated aminated 64852-22-8	Not Established	Not Established	Not Established
Trade Secret	Not Established	Not Established	Not Established
Titanium dioxide 13463-67-7	15 mg/m ³ TWA (total dust)	10 mg/m ³ TWA	Not Established
Polyether Polyol 25791-96-2	Not Established	Not Established	Not Established
Carbon Black 1333-86-4	3.5 mg/m ³ TWA	3 mg/m ³ TWA (inhalable fraction)	NIOSH: 3.5 mg/m ³ TWA; 0.1 mg/m ³ TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)

Engineering Controls: General mechanical ventilation is sufficient for most conditions. Control airborne levels below the exposure guidelines, if established.

Local exhaust ventilation may be necessary for some operations.

General Hygiene Considerations: Wash thoroughly after handling and before eating, drinking or smoking.

Eye/face Protection: Use chemical safety glasses, splash-proof eye goggles or goggles with full faceshield.

Skin Protection: Use nitrile or other impermeable chemical resistant gloves to prevent skin irritation. If potential for skin contact is present, wear impervious, long-sleeved, body covering clothing and rubber boots.

Respiratory Protection: Respiratory protection should not be needed. If exposure may or does exceed occupational exposure limits, respiratory irritation is experienced, or during spray application, use a properly fitted MSHA/NIOSH approved respirator fitted with organic vapor cartridges. In addition, spray application may require the use of paint pre-filters. If the respirator is the sole means of protection, use a full-face supplied air respirator. If sanding or grinding on cured material, use above respirator fitted with HEPA filters or a dust mask.

Contaminated Gear: Remove contaminated clothing and shoes while washing. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

9. Physical and Chemical Properties

Appearance Product color varies	Odor Ammonia-like
Odor Threshold No data found	Physical State Liquid
pH No data found	Melting/Freezing Point No data found
Boiling Point No data found	Boiling Range No data found
Flash Point >212°F, >100°C	Evaporation Rate No data found
Flammability (solid, gas) No data found	LEL/UEL No data found
Vapor Pressure No data found	Vapor Density No data found
Specific Gravity 0.9 - 1.1	Solubility in Water No data found
Partition Coefficient (n-octanol/water) No data found	Autoignition Temperature No data found
Decomposition Temperature No data found	Viscosity No data found
Lbs VOC/Gallon Less Water 0.0	

10. Stability and Reactivity

Chemical Stability: Stable under recommended storage conditions (see Section 7).

Conditions to Avoid: Elevated temperatures may cause product to decompose.

Incompatible Materials: Strong acids, bases, or oxidizing agents. Avoid unintended contact with isocyanates and/or epoxies.

Products of Combustion: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, phenolics, ammonia, nitrogen oxides and other unidentified toxic and/or irritating compounds.

Hazardous polymerization will not occur.

11. Toxicological Information

Mixture Toxicity

Oral Toxicity LD50: 2,181mg/kg

Dermal Toxicity LD50: 3,574mg/kg

Component Toxicity

9046-10-0

Polyoxyalkyleneamine

Oral LD50: 2,885 mg/kg (Rat) Dermal LD50: 2,980 mg/kg (Rabbit)

68479-98-1

Diethyltoluenediamine

Oral LD50: 738 mg/kg (Rat) Dermal LD50: 2,017 mg/kg (Rat)

25791-96-2

Polyether Polyol

Oral LD50: 2,001 mg/kg (Rat) Dermal LD50: 2,001 mg/kg (Rabbit) Inhalation LC50: 801 mg/L

Toxicological information on this product or its components appear in this section when such data is available.

Exposure to amine vapor has been reported to cause transient corneal edema described as blue haze, halo effect, foggy or blurred vision for several hours. This condition is typically temporary and does not cause permanent visual effects.

When the proper eye protection specified in Section 8 is worn, exposure is significantly reduced and the condition has not been observed.

Likely Routes of Exposure:

No data found

Target Organs

May cause damage to the following organs:

Eyes Respiratory System

Effects of Overexposure

Carcinogenicity: Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2b) through inhalation (not ingestion), based on lifetime inhalation studies of rats. The IARC's findings were consistent with the massive accumulation of fine dust particles in the rat's lung (which overwhelm the natural lung clearance mechanisms, causing lung overloading) and consequential pulmonary overload and inflammation that causes lung cancer. In further studies, these tumors were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. Epidemiology studies on more than 20,000 workers do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. If present in this product, the titanium dioxide is in a "wet out" form and does not pose an inhalation hazard.

Carcinogenicity: This product may contain carbon black, a substance that has been listed by OSHA as a carcinogen to humans when inhaled. If present in this product, it is pre-dispersed in a liquid and not available as a dust. Under normal use conditions it would not be considered a hazard. IARC characterized carbon black as a possible human carcinogen (Group 2B) and concluded that there is sufficient evidence in experimental animals for the carcinogenicity of inhaled carbon black dust and inadequate evidence of carcinogenicity in humans. The IARC's findings were consistent with the massive accumulation of fine dust particles in the lung which overwhelm the natural lung clearance mechanisms, known as "lung overload" phenomenon, rather than from a specific chemical effect from the carbon black in the lung. NIOSH recommends that only carbon blacks with a PAH level greater than 0.1% be considered potential occupational carcinogens.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
1333-86-4	Carbon Black	0 - 1%	Carbon Black: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed
13463-67-7	Titanium dioxide	0 - 5%	Titanium dioxide: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed

12. Ecological Information

Component Ecotoxicity

Polyoxyalkyleneamine	96 Hr LC50 Oncorhynchus mykiss: > 15 mg/L [semistatic] 48 Hr EC50 Daphnia magna: 80 mg/L [Static] 96 Hr ErC50 Pseudokirchneriella subcapitata: 15 mg/L
Diethyltoluenediamine	96 Hr LC50 fish: >104 mg/L 48 Hr EC50 water flea: 5.8 mg/L 72 Hr EC50 algae: 104 mg/L
Glycerine, propoxylated aminated	96 Hr LC50 fish: 68 mg/L

13. Disposal Considerations

Waste Disposal Methods: Dispose of in accordance with federal, state and local regulations. The preferred method for disposal of uncontaminated product is by recycling, reclaiming, incineration or other thermal destruction device using a licensed and permitted waste disposal contractor.

14. Transport Information

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Not Regulated			
ICAO/IATA	Not Regulated			
IMDG	Not Regulated			
TDG	Not Regulated			
MOT	Not Regulated			

15. Regulatory Information

USA Federal: This SDS has been prepared in compliance with the Occupational Safety and Health Act (OSHA) Hazard Communication Standard (29 CFR 1910.1200). This product is considered to be a hazardous chemical under that standard. The specific chemical identity and/or exact percentage of any proprietary ingredient(s) may be withheld as a trade secret, pursuant to the standard.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986): To the best of our knowledge, this product contains the following chemicals which are known to the State of California to cause cancer, developmental or reproductive toxicity at levels which require warning under this statute:

1333-86-4 Carbon Black 0 to 1 % Carcinogen
 13463-67-7 Titanium dioxide 0 to 5 % Carcinogen

USA Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) - section 103 Hazardous Substances Reportable Quantities (RQs): To the best of our knowledge, this product contains the following chemicals which are listed in 40 CFR 302.4:

- None

Massachusetts Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

1333-86-4 Carbon Black 0 to 1 %
 13463-67-7 Titanium dioxide 0 to 5 %

New Jersey Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

1333-86-4 Carbon Black 0 to 1 %
 13463-67-7 Titanium dioxide 0 to 5 %

Pennsylvania Right to Know: To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

1333-86-4 Carbon Black 0 to 1 %
 13463-67-7 Titanium dioxide 0 to 5 %

USA Resource Conservation and Recovery Act (40 CFR 261): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

USA Superfund Amendments and Reauthorization Act (SARA) of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 313 Toxic Release Inventory (TRI) Form R: To the best of our knowledge, this product contains the following chemicals which are listed in 40 CFR 372.65:

- None

USA Superfund Amendments and Reauthorization Act (SARA) of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) - section 302 Extremely Hazardous Substances Threshold Planning Quantities (TPQs): To the best of our knowledge, this product contains the following chemicals at levels which require reporting under this statute:

- None

USA Toxic Substances Control Act (TSCA) - section 12(b): To the best of our knowledge, this product contains the following chemicals above the de minimus concentration(s) which requires notification to the Environmental Protection Agency (EPA) per 40 CFR 707, subpart D, if any person intends to export:

68479-98-1 Diethyltoluenediamine 10 to 30 %

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Canada Domestic Substance List	Yes
Canada	Canada Non-Domestic Substances List (NDSL)	No
China	China Inventory of Existing Chemical Substances	Yes
EU	EU REACH List of Registered Intermediates	No
EU	EU REACH List of Pre-Registered Substances	Yes
EU	EU REACH List of Registered Substances	Yes
Japan	Japanese Existing and New Chemical Substances List	No
South Korea	South Korea Existing Chemicals Inventory	No
Philippines	Philippines Inventory of Chemicals and Chemical	No
USA	USA TSCA Inventory list section 8(b)	Yes

- None

16. Other Information

Legend

ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
ADR/RID	European Agreement for transport of dangerous goods by road (ADR) and by rail (RID)
AICS	Australia Inventory of Chemical Substances
CAS No.	Chemical Abstract Service Registry Number
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act, AKA "Superfund"
DOT	Department of Transportation (USA)
DLS	Canada Domestic Substances List
ENCS	Japan Existing and New Chemical Substances
HCS	OSHA Hazard Communication Standard (29 CFR 1910.1200)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IECS	China Inventory of Existing Chemical Substances
IMO	International Maritime Organization
IMDG	International Maritime Dangerous Goods
KECI	Korea Existing Chemicals Inventory - Annex 1
MOT	Thailand Ministry of Transport
MSHA	Mine Safety and Health Administration
N.A.	Not Applicable
NDSL	Canada Non-Domestic Substances List
N.D.	Not Determined
N.E.	Not Established
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration (USA)


PEL	Permissible Exposure Limit
PICCS	Philippines Inventory of Chemicals and Chemical Substances
SARA	Superfund Amendments and Reauthorization Act of 1986 (40 CFR)
STEL	Short Term Exposure Limit (15 minute Time Weighted Average)
TDG	Canada Transport of Dangerous Goods regulations
TLV	Threshold Limit Value
TWA	Time Weighted Average
WHMIS	Canada Workplace Hazardous Materials Information System

Hazardous Material Information System (HMIS)

HEALTH	<input type="text" value="2"/>
FLAMMABILITY	<input type="text" value="1"/>
PHYSICAL HAZARD	<input type="text" value="0"/>
PERSONAL PROTECTION	<input type="text" value=""/>

HMIS & NFPA Hazard Rating Legend
 * = Chronic Health Hazard
 0 = INSIGNIFICANT
 1 = SLIGHT
 2 = MODERATE
 3 = HIGH

National Fire Protection Association (NFPA)



Disclaimer

VERSAFLEX MAKES NO REPRESENTATIONS OR WARRANTIES WITH RESPECT TO ANY INFORMATION PRESENTED HEREIN, ALL OF WHICH IS PROVIDED "AS IS". TO THE MAXIMUM EXTENT PERMITTED BY LAW, VERSAFLEX EXPRESSLY EXCLUDES ALL WARRANTIES, OBLIGATIONS, REPRESENTATIONS, LIABILITIES, TERMS AND CONDITIONS (WHETHER THEY ARE EXPRESS OR IMPLIED, OR ARISE IN CONTRACT, STATUTE, OR OTHERWISE, AND IRRESPECTIVE OF THE NEGLIGENCE OF VERSAFLEX, ITS EMPLOYEES OR AGENTS) IN CONNECTION WITH THE INFORMATION PRESENTED HEREIN. VERSAFLEX MAKES NO REPRESENTATIONS OR WARRANTIES AS TO MERCHANTABILITY, FITNESS FOR PURPOSE, NONINFRINGEMENT OR CONFORMITY WITH DESCRIPTION OR SAMPLE.

Reviewer Revision

Date Prepared: 10/26/2021